

### Overview

#### Models

HP 9512 Switch Chassis	JC125f
HP 9508-V Switch Chassis	JC474f
HP 9505 Switch Chassis	JC124f

#### Key features

- Data center, large campus, enterprise LANs, MANs
- Modular routing switch, IPv6, MPLS
- Future-proof architecture
- Added functionality with service modules
- Robust network and service virtualization

#### Product overview

The HP 9500 Switch Series is a family of modular switches that form a next-generation data center/large campus core switching platform. With unprecedented levels of networking performance, industry-leading availability, and flexible and efficient deployment options, these switches enable new services while driving down the cost of network operations. The 9500 series switches can provide more than 1.4 TB of high-performance switching capacity, aggregate up to 192 10-GbE or 576 GbE ports, and offer a future-proof architecture that enables customers to support emerging enterprise core or data center requirements.

#### Features and benefits

##### Quality of Service (QoS)

- **IEEE 802.1p prioritization:** delivers data to devices based on the priority and type of traffic
- **Class of Service (CoS):** sets the IEEE 802.1p priority tag based on IP address, IP Type of Service (ToS), Layer 3 protocol, TCP/UDP port number, source port, and DiffServ
- **Virtual Output Queuing (VOQ) architecture:** reduces complexity and increases efficiency and cost-effectiveness by eliminating head-of-line blocking issues within the queuing system
- **Bandwidth shaping:**
  - **Port-based rate limiting:** provides per-port ingress-/egress-enforced maximum bandwidth
  - **Classifier-based rate limiting:** uses access control list (ACL) to enforce maximum bandwidth for ingress/egress traffic on each port
- **Traffic policing:** supports Committed Access Rate (CAR) and line rate
- **Congestion avoidance:** Weighted Random Early Detection (WRED)/Random Early Detection (RED)
- **Powerful QoS feature:** supports the following congestion actions: strict priority queuing (SP), weighted round robin (WRR), and SP+WRR

##### Firewall

- **Stateful firewall:** enforces firewall policies to control traffic and filter access to network services; maintains session information for every connection passing through it, enabling the firewall to control packets based on existing sessions
- **Zone-based access policies:** logically groups virtual LANs (VLANs) into zones that share common security policies; allows both unicast and multicast policy settings by zones instead of by individual VLANs
- **Application-level gateway (ALG):** deep packet inspection in the firewall discovers the IP address and service port information

### Overview

embedded in the application data; the firewall then dynamically opens appropriate connections for specific applications

- **NAT/PAT:** choice of dynamic or static network address translation (NAT) preserves a network's IP address pool or conceals the private address of network resources, such as Web servers, which are made accessible to users of a guest or public wireless LAN

### Virtual private network (VPN)

- **IPSec:** provides secure tunneling over an untrusted network such as the Internet or a wireless network; offers data confidentiality, authenticity, and integrity between two endpoints of the network
- **Layer 2 Tunneling Protocol (L2TP):** an industry standard-based traffic encapsulation mechanism supported by many common operating systems such as Windows® XP and Windows Vista®; will tunnel the Point-to-Point Protocol (PPP) traffic over the IP and non-IP networks; may use the IP/UDP transport mechanism in IP networks
- **Generic Routing Encapsulation (GRE):** can be used to transport Layer 2 connectivity over a Layer 3 path in a secured way; enables the segregation of traffic from site to site
- **Manual or automatic Internet Key Exchange (IKE):** provides both manual or automatic key exchange required for the algorithms used in encryption or authentication; auto-IKE allows automated management of the public key exchange, providing the highest levels of encryption

### Management

- **Management interface control:** provides management access through a modem port and terminal interface, as well as in-band and out-of-band Ethernet ports; provides access through terminal interface, telnet, or Secure Shell (SSH)
- **Industry-standard CLI with a hierarchical structure:** reduces training time and expenses, and increases productivity in multivendor installations
- **Management security:** multiple privilege levels with password protection restrict access to critical configuration commands; ACLs provide telnet and SNMP access; local and remote syslog capabilities allow logging of all access
- **SNMPv1, v2, and v3:** provide complete support of SNMP; provide full support of industry-standard Management Information Base (MIB) plus private extensions; SNMPv3 supports increased security using encryption
- **sFlow (RFC 3176):** provides scalable ASIC-based wire-speed network monitoring and accounting with no impact on network performance; this allows network operators to gather a variety of sophisticated network statistics and information for capacity planning and real-time network monitoring purposes
- **Remote monitoring (RMON):** uses standard SNMP to monitor essential network functions; supports events, alarm, history, and statistics group plus a private alarm extension group
- **FTP, TFTP, and SFTP support:** FTP allows bidirectional transfers over a TCP/IP network and is used for configuration updates; Trivial FTP is a simpler method using User Datagram Protocol (UDP)
- **Debug and sampler utility:** supports ping and traceroute for both IPv4 and IPv6
- **Network Quality Analyzer (NQA):** analyzes network performance and service quality by sending test packets, and provides network performance and service quality parameters such as jitter, TCP, or FTP connection delays and file transfer rates; allows a network manager to determine overall network performance and to diagnose and locate network congestion points or failures
- **Network Time Protocol (NTP):** synchronizes timekeeping among distributed time servers and clients; keeps consistent timekeeping among all clock-dependent devices within the network so that the devices can provide diverse applications based on the consistent time
- **Info center:** provides a central information center for system and network information; aggregates all logs, traps, and debugging information generated by the system and maintains them in order of severity; outputs the network information to multiple channels based on user-defined rules
- **IEEE 802.1AB Link Layer Discovery Protocol (LLDP):** automated device discovery protocol provides easy mapping of network management applications
- **Multiple configuration files:** can be stored to the flash image
- **Dual flash images:** provide independent primary and secondary operating system files for backup while upgrading
- **USB support:**

### Overview

- **File copy:** allows users to copy switch files to and from a USB flash drive

### Connectivity

- **High-density port connectivity:** provides up to 12 interface module slots, up to 192 10-GbE ports, or 576 GbE ports (fiber or copper) per system
- **Flexible port selection:** provides a combination of fiber and copper interface modules, 100/1000BASE-X auto-speed selection, and 10/100/1000BASE-T auto-speed detection plus auto duplex and MDI/MDI-X
- **Jumbo frames:** are supported on 10 GbE and GbE ports; up to 9,000 sizes allow high-performance backups and disaster-recovery systems
- **Loopback:** supports internal loopback testing for maintenance purposes and an increase in availability; loopback detection protects against incorrect cabling or network configurations and can be enabled on a per-port or per-VLAN basis for added flexibility
- **Packet storm protection:** protects against broadcast, multicast, or unicast storms with user-defined thresholds
- **Ethernet OAM:** provides a Layer 2 link performance and fault detection monitoring tool, which reduces failover and network convergence times
- **Flow control:** using standard IEEE 802.3x, it provides back pressure to reduce congestion in heavy traffic situations
- **Monitor link:** collects statistics on performance and errors on physical links, increasing system availability

### Performance

- **Scalable system design:** backplane is designed for bandwidth increases; provides investment protection to support future technologies and higher-speed connectivity
- **Flexible chassis selection:** provides a choice of three chassis, ranging from a 12-slot or 8-slot vertical chassis for data center applications and a 5-slot chassis; allows you to tailor your needs to meet your budget
- **High-speed fully distributed architecture:** provides switching capacity up to 1440 Gbps; supports a bandwidth of 857 Mpps and up to 192 10-GbE ports or 576 GbE fiber or copper ports; all switching and routing is performed in the I/O modules; meets today's and future demand for an enterprise's bandwidth-intensive applications

### Resiliency and high availability

- **Redundant/Load-sharing fabrics, management, fan assemblies, and power supplies:** increase total performance and power available while providing hitless, stateful failover
- **Hot-swappable modules:** help ensure the replacement of hardware interface modules without impacting the traffic flow through the system
- **Redundant power supplies:** services module has the same level of power supply redundancy as the switch in which it is installed
- **Passive design system:** backplane has no active components for increased system reliability
- **Separate data and control paths:** increases security and performance
- **Hitless patch upgrades:** allow patches and new service features to be installed without restarting the equipment, increasing network uptime and facilitating maintenance
- **IEEE 802.3ad Link Aggregation Control Protocol (LACP):** supports up to 240 trunks, each with 12 links per trunk; supports static or dynamic groups and user-selectable hashing algorithm
- **Virtual Router Redundancy Protocol (VRRP):** allows a group of routers to dynamically back each other up to create highly available routed environments
- **Intelligent Resilient Framework (IRF):** creates virtual resilient switching fabrics, where two or more switches perform as a single Layer 2 switch and Layer 3 router; switches do not have to be co-located and can be part of a disaster-recovery system; servers or switches can be attached using standard LACP for automatic load balancing and high availability; simplifies network operation by eliminating the complexity of Spanning Tree Protocol, Equal-Cost Multipath (ECMP), or VRRP

### Overview

- **Smart link:** allows 50 ms failover between links
- **Graceful restart:** features are fully supported, including graceful restart for OSPF, IS-IS, BGP, LDP, and RSVP; network remains stable during the active-standby switchover; after the switchover, the device quickly learns the network routes by communicating with adjacent routers; forwarding remains uninterrupted during the switchover to realize nonstop forwarding (NSF)
- **IP/LDP FRR:** nodes are configured with backup ports, routes, and LSPs; local implementation requires no cooperation of adjacent devices, simplifying the deployment; solves the traditional convergence faults in IP forwarding and MPLS forwarding, protecting the links, nodes, and paths without establishing respective backup LSPs for them; realizes restoration within 50 ms, with the restoration time independent of the number of routes and fast link switchovers, without route convergence
- **Ring Resiliency Protection Protocol (RRPP):** provides standard sub-200 ms recovery for ring Ethernet-based topology

### Layer 2 switching

- **VLANs:** support up to 4,096 port or IEEE 802.1Q-based VLANs
- **Spanning Tree Protocol:** fully supports standard IEEE 802.1D Spanning Tree Protocol, IEEE 802.1w Rapid Spanning Tree Protocol for faster convergence, and IEEE 802.1s Multiple Spanning Tree Protocol
- **Internet Group Management Protocol (IGMP) and Multicast Listener Discovery (MLD) protocol snooping:** effectively control and manage the flooding of multicast packets in a Layer 2 network
- **Port isolation:** increases security by isolating ports within a VLAN while still allowing them to communicate with other VLANs
- **GARP VLAN Registration Protocol:** allows automatic learning and dynamic assignment of VLANs
- **Bridge Protocol Data Unit (BPDU) tunneling:** transmits Spanning Tree Protocol BPDUs transparently, allowing correct tree calculations across service providers, WANs, or MANs
- **Port mirroring:** duplicates port traffic (ingress and egress) to a local or remote monitoring port; supports 64 mirroring groups, with an unlimited number of ports per group
- **Device Link Detection Protocol (DLDP):** monitors link connectivity and shuts down ports at both ends if uni-directional traffic is detected, preventing loops in STP-based networks
- **IEEE 802.1ad QinQ and Selective QinQ:** increase the scalability of an Ethernet network by providing a hierarchical structure; connect multiple LANs on a high-speed campus or metro network

### Layer 3 services

- **Address Resolution Protocol (ARP):** determines the MAC address of another IP host in the same subnet; supports static ARPs; gratuitous ARP allows detection of duplicate IP addresses; proxy ARP allows normal ARP operation between subnets or when subnets are separated by a Layer 2 network
- **User Datagram Protocol (UDP) helper:** redirects UDP broadcasts to specific IP subnets to prevent server spoofing
- **Dynamic Host Configuration Protocol (DHCP):** simplifies the management of large IP networks and supports client and server; DHCP Relay enables DHCP operation across subnets

### Layer 3 routing

- **Static IPv4 routing:** provides simple, manually configured IPv4 routing
- **Routing Information Protocol:** uses a distance vector algorithm with UDP packets for route determination; supports RIPv1 and RIPv2 routing; includes loop protection
- **OSPF:** Interior Gateway Protocol (IGP) uses link-state protocol for faster convergence; supports ECMP, NSSA, and MD5 authentication for increased security and graceful restart for faster failure recovery
- **Border Gateway Protocol 4 (BGP-4):** Exterior Gateway Protocol (EGP) with path vector protocol uses TCP for enhanced reliability for the route discovery process, reduces bandwidth consumption by advertising only incremental updates, and supports extensive policies for increased flexibility, as well as scales to very large networks
- **Intermediate system to intermediate system (IS-IS):** Interior Gateway Protocol (IGP) uses path vector protocol, which is

### Overview

defined by the ISO organization for IS-IS routing and extended by IETF RFC 1195 to operate in both TCP/IP and the OSI reference model (Integrated IS-IS)

- **Policy-based routing:** makes routing decisions based on policies set by the network administrator
- **IP performance enhancement:** is a set of tools that enhances the performance of IPv4 networks; includes directed broadcasts, customization of TCP parameters, support of ICMP error packets, and extensive display capabilities
- **Unicast Reverse Path Forwarding (uRPF):** is defined by RFC 3704 and limits erroneous or malicious traffic
- **Static IPv6 routing:** provides simple, manually configured IPv6 routing
- **Dual IP stack:** maintains separate stacks for IPv4 and IPv6 to ease transition from an IPv4-only network to an IPv6-only network design
- **Routing Information Protocol next generation (RIPng):** extends RIPv2 to support IPv6 addressing
- **OSPFv3:** provides OSPF support for IPv6
- **IS-IS for IPv6:** extends IS-IS to support IPv6 addressing
- **BGP+:** extends BGP-4 to support Multiprotocol BGP (MBGP), including support for IPv6 addressing
- **IPv6 tunneling:** is an important element for the transition from IPv4 to IPv6; allows IPv6 packets to traverse IPv4-only networks by encapsulating the IPv6 packet into a standard IPv4 packet; supports manually configured, 6to4, and Intra-Site Automatic Tunnel Addressing Protocol (ISATAP) tunnels
- **Multiprotocol Label Switching (MPLS):** uses BGP to advertise routes across Label Switched Paths (LSPs), but uses simple labels to forward packets from any Layer 2 or Layer 3 protocol, thus reducing complexity and increasing performance; supports graceful restart for reduced failure impact; supports LSP tunneling and multilevel stacks
- **Multiprotocol Label Switching (MPLS) Layer 3 VPN:** allows Layer 3 VPNs across a provider network; uses MP-BGP to establish private routes for increased security; supports RFC 2547bis multiple autonomous system VPNs for added flexibility
- **Multiprotocol Label Switching (MPLS) Layer 2 VPN:** establishes simple Layer 2 point-to-point VPNs across a provider network using only MPLS LDPs; requires no routing and therefore decreases complexity, increases performance, and allows VPNs of non-routable protocols; uses no routing information for increased security; supports Martini draft technologies
- **Virtual Private LAN Service (VPLS):** establishes point-to-multipoint Layer 2 VPNs across a provider network
- **Multiprotocol Label Switching Traffic Engineering (MPLS TE):** Traffic Engineering (TE) is used to enhance traffic over large MPLS networks based on type of traffic and available resources; TE dynamically tunes traffic management attributes and enables true load balancing; MPLS TE supports route backup using Fast Reroute (FRR)
- **Service loopback:** allows any module to take advantage of higher-featured modules, including OAA modules, by redirecting traffic; reduces investment and enables higher bandwidth and load sharing; supports IPv6, IPv6 multicast, tunneling, and MPLS
- **Bidirectional Forwarding Detection (BFD):** enables link connectivity monitoring and reduces network convergence time for RIP, OSPF, BGP, IS-IS, VRRP, MPLS, and IRF
- **Multicast VPN:** supports Multicast Domain (MD) multicast VPN, which can be distributed on separate service cards, providing high performance and flexible configuration

### Security

- **DHCP protection:** blocks DHCP packets from unauthorized DHCP servers, preventing denial-of-service attacks
- **DHCP snooping:** helps ensure that DHCP clients receive IP addresses from authorized DHCP servers and maintain a list of DHCP entries for trusted ports; prevents reception of fake IP addresses and reduces ARP attacks, improving security
- **RADIUS:** eases switch security access administration by using a password authentication server
- **TACACS+:** is an authentication tool using TCP with encryption of the full authentication request that provides additional security
- **Switch management logon security:** can require either RADIUS or TACACS+ authentication for secure switch CLI logon
- **Media access control (MAC) authentication:** provides simple authentication based on a user's MAC address; supports local or RADIUS-based authentication
- **Secure Shell (SSHv2):** uses external servers to securely log in to a remote device; with authentication and encryption, it protects against IP spoofing and plain-text password interception; increases the security of Secure FTP (SFTP) transfers
- **Attack protection:** protects network from attacks that use a large number of ARP requests by using a host-specific, user-selectable threshold; provides Address Scanning Attack Prevention, MAC Address Flooding Attack Prevention, and STP Attack

### Overview

#### Prevention

- **Access control list (ACL):** supports powerful ACLs for both IPv4 and IPv6; filters traffic to prevent unauthorized users from accessing the network, or controls network traffic to save resources; rules can either deny or permit traffic to be forwarded; rules can be based on Layer 2 header or Layer 3 protocol header; rules can be set to operate on specific dates or times
- **IP Source Guard:** filters packets on a per-port basis, which prevents illegal packets from being forwarded
- **Network address translation (NAT):** provides a method for translating private IP addresses to public IP addresses, reducing the number of IP addresses used, and isolates the enterprise addressing environment
- **Multiple user authentication methods:**
  - **IEEE 802.1X:** is an industry-standard method of user authentication using an IEEE 802.1X supplicant on the client in conjunction with a RADIUS server
  - **Web-based authentication:** similar to IEEE 802.1X, it provides a browser-based environment to authenticate clients that do not support the IEEE 802.1X supplicant
  - **MAC-based authentication:** authenticates the client with the RADIUS server based on the client's MAC address
- **Endpoint Admission Defense (EAD):** provides security policies to users accessing a network
- **Port isolation:** secures and adds privacy, and prevents malicious attackers from obtaining user information

### Convergence

- **Multicast Source Discovery Protocol (MSDP):** is used for inter-domain multicast applications, allowing multiple PIM-SM domains to interoperate
- **Internet Group Management Protocol (IGMP):** is used by IP hosts to establish and maintain multicast groups; supports IGMPv1, v2, and v3; utilizes Any-Source Multicast (ASM) or Source-Specific Multicast (SSM) to manage IPv4 multicast networks
- **Protocol Independent Multicast (PIM):** is used for IPv4 and IPv6 multicast applications; supports PIM Dense Mode (PIM-DM), Sparse Mode (PIM-SM), and Source-Specific Mode (PIM-SSM)
- **Multicast Border Gateway Protocol (MBGP):** allows multicast traffic to be forwarded across BGP networks and kept separate from unicast traffic
- **Multicast Listener Discovery (MLD) protocol:** is used by IP hosts to establish and maintain multicast groups; supports v1 and v2 and utilizes Any-Source Multicast (ASM) or Source-Specific Multicast (SSM) to manage IPv6 multicast networks
- **Multicast VLAN:** allows multiple VLANs to receive the same IPv4 or IPv6 multicast traffic, reducing network bandwidth demand by eliminating multiple streams to each VLAN

### Integration

- **Open Application Architecture (OAA):** provides high-performance application-specific modules fully integrated with the switching architecture; uses the chassis high-speed backplane to access network-related data; increases performance, reduces costs, and simplifies network management
- **VPN firewall module:** provides enhanced stateful packet inspection and filtering; supports flexible security zones and virtual firewall containment; provides advanced VPN services with 3DES and AES encryption at high performance and low latency, Web content filtering, and application prioritization and enhancement
- **Load-balancing module:** local and global server load-balancing module improves traffic distribution using powerful scheduling algorithms, including Layer 4 to 7 services; monitors the health status of servers and firewalls
- **NetStream module:** provides traffic analysis and statistics capture to allow network administrators to rapidly identify network anomalies and security threats, as well as capacity planning information; supports NetFlow v5 and v9
- **Wireless controller module:** supports up to 640 access points (APs) per module; supports IEEE 802.11s/b/g/n APs; provides full user access management and QoS policies on a per-user basis; supports enterprise-class encryption; supports RF monitoring and control, MAP control, rogue AP detection, and location policy enforcement

### Additional information



### Overview

- **Green initiative support:** provides support for RoHS and WEEE regulations
- **Low power consumption:** is rated to have one of the lowest power usages in the industry by Miercom independent tests
- **Unified, modular Comware operating system with modular architecture:** all switching, routing, and security platforms leverage Comware, a common unified modular operating system; provides an easy-to-enhance-and-extend feature set without wholesale changes
- **OPEX savings:** is a common operating system that simplifies and streamlines deployment, management, and training, thereby cutting costs as well as reducing the chance for human errors associated with having to manage multiple operating systems across different platforms and network layers

### Warranty and support

- **1-year warranty:** with advance replacement and 10-calendar-day delivery (available in most countries)
- **Electronic and telephone support:** limited electronic and telephone support is available from HP; to reach our support centers, refer to [www.hp.com/networking/contact-support](http://www.hp.com/networking/contact-support); for details on the duration of support provided with your product purchase, refer to [www.hp.com/networking/warrantysummary](http://www.hp.com/networking/warrantysummary)
- **Software releases:** to find software for your product, refer to [www.hp.com/networking/support](http://www.hp.com/networking/support); for details on the software releases available with your product purchase, refer to [www.hp.com/networking/warrantysummary](http://www.hp.com/networking/warrantysummary)

### Configuration

#### Build To Order:

**BTO is a standalone unit with no integration. BTO products ship standalone are not part of a CTO or Rack-Shippable solution.**

HP 9505 Switch Chassis	JC124B
<ul style="list-style-type: none"><li>• 5 - I/O module slots</li><li>• Must select min 1 Power Supply</li></ul>	
HP 9508-V Switch Chassis	JC474B
<ul style="list-style-type: none"><li>• 8 - I/O module slots</li><li>• Must select min 1 Power Supply</li></ul>	
HP 9512 Switch Chassis	JC125B
<ul style="list-style-type: none"><li>• 12 - I/O module slots</li><li>• Must select min 1 Power Supply</li></ul>	

### Modules

#### Ethernet Modules

(JC124B Switch Only) System (std 0 // max 5) User Selection (min 0 // max 5) per enclosure

(JC474B Switch Only) System (std 0 // max 8) User Selection (min 0 // max 8) per enclosure

(JC125B Switch Only) System (std 0 // max 12) User Selection (min 0 // max 12) per enclosure

HP 9500 16-port 10GbE SFP+ Module	JC108A
<ul style="list-style-type: none"><li>• min=0 \ max=16 SFP + Transceivers</li></ul>	See Configuration Note:2
HP 9500 4-port 10GbE XFP Module	JC114A
<ul style="list-style-type: none"><li>• min=0 \ max=4 XFP Transceivers</li></ul>	See Configuration Note:3
HP 9500 2-port 10GbE XFP Module	JC112A
<ul style="list-style-type: none"><li>• min=0 \ max=2 XFP Transceivers</li></ul>	See Configuration Note:3
HP 9500 48-port GbE SFP Module	JC113A
<ul style="list-style-type: none"><li>• min=0 \ max=48 SFP Transceivers</li></ul>	See Configuration Note:1
HP 9500 24-port GbE SFP Module	JC123A
<ul style="list-style-type: none"><li>• min=0 \ max=24 SFP Transceivers</li></ul>	See Configuration Note:1

### Configuration

HP 9500 48-port Gig-T Module	JC107A
<ul style="list-style-type: none"><li>No Transceivers</li></ul>	
HP 9500 48-port Gig-T 2.4:1 Module	JC116A
<ul style="list-style-type: none"><li>No Transceivers</li></ul>	
HP 9500 24-port Gig-T Module	JC122A
<ul style="list-style-type: none"><li>min=0 \ max=24 SFP Transceivers</li></ul>	See Configuration Note:1
HP 9500 4-port 10GbE XFP Advanced Module	JC118A
<ul style="list-style-type: none"><li>min=0 \ max=4 XFP Transceivers</li></ul>	See Configuration Note:3
HP 9500 2-p 10GBASE-X XFP Advanced Mod	JC470A
<ul style="list-style-type: none"><li>min=0 \ max=2 XFP Transceivers</li></ul>	See Configuration Note:3
HP 9500 48p 1000BASE-X SFP Advanced Mod	JC471A
<ul style="list-style-type: none"><li>min=0 \ max=48 SFP Transceivers</li></ul>	See Configuration Note:1
HP 9500 24-port GbE SFP Advanced Module	JC117A
<ul style="list-style-type: none"><li>min=0 \ max=24 SFP Transceivers</li></ul>	See Configuration Note:1
HP 9500 48-port Gig-T Advanced Module	JC115A
<ul style="list-style-type: none"><li>No Transceivers</li></ul>	
HP 9500 24-port Gig-T Advanced Module	JC119A
<ul style="list-style-type: none"><li>min=0 \ max=24 SFP Transceivers</li></ul>	See Configuration Note:1
HP 9500 Access Controller Module for 128-640 Aps	JD442A
<ul style="list-style-type: none"><li>No Transceivers</li></ul>	
HP 9500 NetStream Monitoring Module	JD246A
<ul style="list-style-type: none"><li>No Transceivers</li></ul>	
HP 9500 Load Balancing Module	JD247A
<ul style="list-style-type: none"><li>No Transceivers</li></ul>	
HP 9500 VPN Firewall Module	JD245A

### Configuration

- min=0 \ max=2 SFP Transceivers

See Configuration  
Note:4

#### Configuration Rules:

Note 1	The following Transceivers install into this Module:	
	HP X170 1G SFP LC LH70 1550 Transceiver	JD109A
	HP X170 1G SFP LC LH70 1570 Transceiver	JD110A
	HP X170 1G SFP LC LH70 1590 Transceiver	JD111A
	HP X170 1G SFP LC LH70 1610 Transceiver	JD112A
	HP X170 1G SFP LC LH70 1470 Transceiver	JD113A
	HP X170 1G SFP LC LH70 1490 Transceiver	JD114A
	HP X170 1G SFP LC LH70 1510 Transceiver	JD115A
	HP X170 1G SFP LC LH70 1530 Transceiver	JD116A
	HP X120 1G SFP LC LH100 Transceiver	JD103A
	HP X125 1G SFP LC LH40 1310nm Transceiver	JD061A
	HP X120 1G SFP LC LH40 1550nm Transceiver	JD062A
	HP X125 1G SFP LC LH70 Transceiver	JD063B
	HP X120 1G SFP RJ45 T Transceiver	JD089B
	HP X120 1G SFP LC SX Transceiver	JD118B
	HP X120 1G SFP LC LX Transceiver	JD119B
	HP X120 1G SFP LC BX 10-U Transceiver	JD098B
	HP X120 1G SFP LC BX 10-D Transceiver	JD099B
	HP X110 100M SFP LC FX Transceiver	JF832A
	HP X110 100M SFP LC FX Transceiver	JF833A
Note 2	The following Transceivers install into this Module:	
	HP X130 10G SFP+ LC SR Transceiver	JD092A
	HP X130 10G SFP+ LC LRM Transceiver	JD093A
	HP X130 10G SFP+ LC LR Transceiver	JD094A
	HP X240 10G SFP+ SFP+ 3m DA Cable	JD097B
	HP X240 10G SFP+ SFP+ 3m DAC Cable	JD097C
	HP X240 10G SFP+ SFP+ 5m DA Cable	JG081B
	HP X240 10G SFP+ SFP+ 5m DAC Cable	JG081C
Note 3	The following Transceivers install into this Module:	
	HP X130 10G XFP SC LR Transceiver	JD108B
	HP X130 10G XFP LC SR Transceiver	JD117B
	HP X130 10G XFP LC ZR 1550nm Transceiver	JD107A
Note 4	The following Transceivers install into this Module:	
	HP X125 1G SFP LC LH40 1310nm Transceiver	JD061A
	HP X120 1G SFP LC LH40 1550nm Transceiver	JD062A
	HP X125 1G SFP LC LH70 Transceiver	JD063B
	HP X120 1G SFP LC SX Transceiver	JD118B

### Configuration

HP X120 1G SFP LC LX Transceiver

JD119B

### Fabric Modules

System (std 0 // max 2) User Selection (min 1 // max 2) per enclosure

See Configuration  
Note:3

HP 9500 360Gbps Fabric Module

- min=0 \ max=2 XFP Transceivers

JC121A

See Configuration  
Note:2

HP 9500 720Gbps Fabric Module

- min=0 \ max=2 XFP Transceivers

JC120A

See Configuration  
Note:1

### Configuration Rules:

Note 1      These Modules install to the following switches only:  
JC125B - HP A9512 Switch Chassis  
JC474B - HP A9508-V Switch Chassis

Note 2      These Modules install to the following switches only:  
JC124B - HP A9505 Switch Chassis

Note 3      Mixing of Fabric Module types is not allowed.

## Transceivers

### SFP Transceivers

HP X125 1G SFP LC LH40 1310nm XCVR

JD061A

HP X120 1G SFP LC LH40 1550nm XCVR

JD062A

HP X120 1G SFP RJ45 T Transceiver

JD089B

HP X120 1G SFP LC SX Transceiver

JD118B

HP X120 1G SFP LC LX Transceiver

JD119B

HP X125 1G SFP LC LH70 Transceiver

JD063B

HP X120 1G SFP LC BX 10-U Transceiver

JD098B

HP X120 1G SFP LC BX 10-D Transceiver

JD099B



### Configuration

HP X120 1G SFP LC LH100 Transceiver	JD103A
HP X170 1G SFP LC LH70 1470 Transceiver	JD113A
HP X170 1G SFP LC LH70 1490 Transceiver	JD114A
HP X170 1G SFP LC LH70 1510 Transceiver	JD115A
HP X170 1G SFP LC LH70 1530 Transceiver	JD116A
HP X170 1G SFP LC LH70 1550 Transceiver	JD109A
HP X170 1G SFP LC LH70 1570 Transceiver	JD110A
HP X170 1G SFP LC LH70 1590 Transceiver	JD111A
HP X170 1G SFP LC LH70 1610 Transceiver	JD112A
HP X110 100M SFP LC FX Transceiver	JF833A
HP X120 100M/1G SFP LC LX Transceiver	JF832A

### **SFP+ Transceivers**

HP X130 10G SFP+ LC SR Transceiver	JD092B
HP X130 10G SFP+ LC LRM Transceiver	JD093B
HP X130 10G SFP+ LC LR Transceiver	JD094B
HP X240 10G SFP+ SFP+ 3m DAC Cable	JD097C
HP X240 10G SFP+ to SFP+ 3m Direct Attach Copper Cable	JD097B
HP X240 10G SFP+ SFP+ 5m DAC Cable	JG081C
HP X240 10G SFP+ to SFP+ 5m Direct Attach Copper Cable	JG081B

### **XFP Transceivers**

HP X130 10G XFP LC ZR 1550nm Transceiver	JD107A
HP X130 10G XFP LC SR Transceiver	JD117B

### Configuration

HP X130 10G XFP LC LR 1310nm Transceiver

JD108B

### Internal Power Supplies

System (std 0 // max 2) User Selection (min 1 // max 2) per switch enclosure

HP 9500/8800 1800W AC Power Supply

- includes 1 x c13, 1800w

JC110B

See Configuration  
Note:1, 2

HP 9500/8800 2000W DC Power Supply

JC029B

See Configuration  
Note:1

HP 9500/8800 3500W DC Power Supply

JC473A

See Configuration  
Note:1

#### Configuration Rules:

Note 1 If 2 power supplies are selected they must be the same Sku number.

Note 2 Localization required. (See Localization Menu for list.)

### Power Supply Power Frame

System (std 0 // max 2) User Selection (min 1 // max 2) per switch enclosure

HP 9500 3500W AC Power Frame

JC111A

See Configuration  
Note:1

#### Configuration Rules:

Note 1 If more than 2 AC Power Supplies are selected Then Min = 2 // Max = 2 of this sku is required.

### Switch Enclosure Options

#### Fans

HP 9512/9505/8800 Spare Fan Assembly

JC109A

HP 9508-V Fan Assembly

JC475A



### Configuration

#### Licenses

HP WX Blade 128 AP License Upgrade JD464B

#### Memory

HP 12500 additional 1 GB SDRAM DDR2 JC071A

#### Compact Flash cards

HP X600 1G Compact Flash Card JC684A  
[See Configuration Note:1](#)

HP X600 512M Compact Flash Card JC685A  
[See Configuration Note:1](#)

HP X600 256M Compact Flash Card JC686A  
[See Configuration Note:1](#)

#### Configuration Rules:

Note 1 These CF Cards are supported on the following Modules only:  
JD245A - HP 9500 VPN Firewall Module

### Technical Specifications

#### HP 9512 Switch Chassis (JC125B)

<b>Included accessories</b>	2 HP 9512/9505/8812/8805 Spare Fan Assembly (JC109A)	
<b>Ports</b>	2 switch fabric slots 12 I/O module slots Supports a maximum of 192 10-GbE ports or 576 autosensing 10/100/1000 ports or 576 SFP ports, with optional module	
<b>Power supplies</b>	2 power supply slots 1 minimum power supply required (ordered separately)	
<b>Fan tray</b>	includes: 2 x JC109A 2 fan tray slots	
<b>Physical characteristics</b>	<b>Dimensions</b>	17.4(w) x 17.72(d) x 29.65(h) in (44.2 x 45.0 x 75.3 cm) (17U height)
	<b>Weight</b>	132.28 lb. (60 kg), Fully loaded chassis, two fabrics, two power supplies, and a full complement of typical I/O modules
	<b>Full configuration weight</b>	242.5 lb. (110 kg)
<b>Memory and processor</b>	<b>Fabric</b>	PowerPC @ 1000 MHz, 128 MB flash, 1 GB RAM, 256 MB compact flash
	<b>I/O Module</b>	PowerPC @ 667 MHz, 512 MB RAM
<b>Mounting</b>	Mounts in an EIA standard 19-in. rack or other equipment cabinet (hardware included); horizontal surface mounting only	
<b>Performance</b>	<b>1000 Mb Latency</b>	< 6.0 $\mu$ s (FIFO 64-byte packets)
	<b>10 Gbps Latency</b>	< 6.0 $\mu$ s (FIFO 64-byte packets)
	<b>Throughput</b>	857 million pps
	<b>Routing/Switching capacity</b>	1440 Gbps
	<b>Routing table size</b>	256000 entries
	<b>Reliability</b>	<b>Availability</b>
<b>Environment</b>	<b>Operating temperature</b>	32°F to 113°F (0°C to 45°C)
	<b>Operating relative humidity</b>	5% to 95%, noncondensing
	<b>Nonoperating/Storage temperature</b>	-40°F to 158°F (-40°C to 70°C)
	<b>Nonoperating/Storage relative humidity</b>	5% to 95%, noncondensing
<b>Electrical characteristics</b>	<b>Voltage</b>	100-120/200-240 VAC
	<b>DC Voltage</b>	-48 V/-60 V
	<b>Current</b>	16/92 A
	<b>Power output</b>	3500 W
	<b>Frequency</b>	50/60 Hz
	<b>Notes</b>	Based on a 3500 W DC power supply
<b>Safety</b>	UL 60950-1; IEC 60950-1; CAN/CSA-C22.2 No. 60950-1; EN 60950-1/A11	

### Technical Specifications

<b>Emissions</b>	VCCI Class A; EN 55022 Class A; ICES-003 Class A; ANSI C63.4 2003; AS/NZS CISPR22 Class A; EN 61000-3-2:2006; EN 61000-3-3:1995 +A1:2001+A2:2005; EMC Directive 2004/108/EC; FCC (CFR 47, Part 15) Class A																						
<b>Immunity</b>	<table border="0"> <tr> <td style="padding-right: 20px;"><b>Generic</b></td> <td>ETSI EN 300 386 V1.3.3</td> </tr> <tr> <td><b>EN</b></td> <td>EN 61000-4-2:1995+A1:1998+A2:2001</td> </tr> <tr> <td><b>ESD</b></td> <td>EN 61000-4-2</td> </tr> <tr> <td><b>Radiated</b></td> <td>EN 61000-4-3</td> </tr> <tr> <td><b>EFT/Burst</b></td> <td>EN 61000-4-4</td> </tr> <tr> <td><b>Surge</b></td> <td>EN 61000-4-5</td> </tr> <tr> <td><b>Conducted</b></td> <td>EN 61000-4-6</td> </tr> <tr> <td><b>Power frequency magnetic field</b></td> <td>IEC 61000-4-8</td> </tr> <tr> <td><b>Voltage dips and interruptions</b></td> <td>EN 61000-4-11</td> </tr> <tr> <td><b>Harmonics</b></td> <td>EN 61000-3-2, IEC 61000-3-2</td> </tr> <tr> <td><b>Flicker</b></td> <td>EN 61000-3-3, IEC 61000-3-3</td> </tr> </table>	<b>Generic</b>	ETSI EN 300 386 V1.3.3	<b>EN</b>	EN 61000-4-2:1995+A1:1998+A2:2001	<b>ESD</b>	EN 61000-4-2	<b>Radiated</b>	EN 61000-4-3	<b>EFT/Burst</b>	EN 61000-4-4	<b>Surge</b>	EN 61000-4-5	<b>Conducted</b>	EN 61000-4-6	<b>Power frequency magnetic field</b>	IEC 61000-4-8	<b>Voltage dips and interruptions</b>	EN 61000-4-11	<b>Harmonics</b>	EN 61000-3-2, IEC 61000-3-2	<b>Flicker</b>	EN 61000-3-3, IEC 61000-3-3
<b>Generic</b>	ETSI EN 300 386 V1.3.3																						
<b>EN</b>	EN 61000-4-2:1995+A1:1998+A2:2001																						
<b>ESD</b>	EN 61000-4-2																						
<b>Radiated</b>	EN 61000-4-3																						
<b>EFT/Burst</b>	EN 61000-4-4																						
<b>Surge</b>	EN 61000-4-5																						
<b>Conducted</b>	EN 61000-4-6																						
<b>Power frequency magnetic field</b>	IEC 61000-4-8																						
<b>Voltage dips and interruptions</b>	EN 61000-4-11																						
<b>Harmonics</b>	EN 61000-3-2, IEC 61000-3-2																						
<b>Flicker</b>	EN 61000-3-3, IEC 61000-3-3																						
<b>Management</b>	IMC - Intelligent Management Center; command-line interface; out-of-band management (serial RS-232C); SNMP Manager; Telnet; terminal interface (serial RS-232C); modem interface; IEEE 802.3 Ethernet MIB; Ethernet Interface MIB																						
<b>Notes</b>	IPSec/IKE functionality provided by HP 9500 VPN/Firewall Module (JD245A)																						
<b>Services</b>	<p>3-year, parts only, global next-day advance exchange (HP763E)</p> <p>3-year, 4-hour onsite, 13x5 coverage for hardware (HP764E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware (HP767E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 SW phone support and SW updates (HP770E)</p> <p>3-year, 24x7 SW phone support, software updates (HP773E)</p> <p>Installation with minimum configuration, system-based pricing (UX033E)</p> <p>4-year, 4-hour onsite, 13x5 coverage for hardware (HP765E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware (HP768E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (HP771E)</p> <p>4-year, 24x7 SW phone support, software updates (HP774E)</p> <p>5-year, 4-hour onsite, 13x5 coverage for hardware (HP766E)</p> <p>5-year, 4-hour onsite, 24x7 coverage for hardware (HP769E)</p> <p>5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (HP772E)</p> <p>5-year, 24x7 SW phone support, software updates (HP775E)</p> <p>3 Yr 6 hr Call-to-Repair Onsite (HP776E)</p> <p>4 Yr 6 hr Call-to-Repair Onsite (HP777E)</p> <p>5 Yr 6 hr Call-to-Repair Onsite (HP778E)</p> <p>1-year, 4-hour onsite, 13x5 coverage for hardware (HR499E)</p> <p>1-year, 4-hour onsite, 24x7 coverage for hardware (HR500E)</p> <p>1-year, 6 hour Call-To-Repair Onsite for hardware (HR503E)</p> <p>1-year, 24x7 software phone support, software updates (HR502E)</p> <p>1-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support and software updates (HR501E)</p>																						

Refer to the HP website at: [www.hp.com/networking/services](http://www.hp.com/networking/services) for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

### Technical Specifications

#### HP 9508-V Switch Chassis (JC474B)

<b>Included accessories</b>	1 HP 9508-V/8808-V Spare Fan Assembly (JC475A)	
<b>Ports</b>	2 switch fabric slots 8 I/O module slots Supports a maximum of 128 10-GbE ports or 384 autosensing 10/100/1000 ports or 384 SFP ports, with optional module	
<b>Power supplies</b>	2 power supply slots 1 minimum power supply required (ordered separately)	
<b>Fan tray</b>	includes: 1 x JC475A 1 fan tray slot	
<b>Physical characteristics</b>	<b>Dimensions</b>	17.17(w) x 17.72(d) x 38.39(h) in (43.6 x 45.0 x 97.5 cm) (22U height)
	<b>Weight</b>	127.87 lb. (58 kg), Fully loaded chassis, two fabrics, two power supplies, and a full complement of typical I/O modules
	<b>Full configuration weight</b>	220.46 lb. (100 kg)
<b>Memory and processor</b>	<b>Fabric</b>	PowerPC @ 1000 MHz, 128 MB flash, 1 GB RAM, 256 MB compact flash
	<b>I/O Module</b>	PowerPC @ 667 MHz, 512 MB RAM
<b>Mounting</b>	Mounts in an EIA standard 19-in. rack or other equipment cabinet (hardware included); horizontal surface mounting only	
<b>Performance</b>	<b>1000 Mb Latency</b>	< 6.0 $\mu$ s (FIFO 64-byte packets)
	<b>10 Gbps Latency</b>	< 6.0 $\mu$ s (FIFO 64-byte packets)
	<b>Throughput</b>	571 million pps
	<b>Routing/Switching capacity</b>	960 Gbps
	<b>Routing table size</b>	256000 entries
	<b>Availability</b>	99.999%
<b>Reliability</b>	<b>Operating temperature</b>	32°F to 113°F (0°C to 45°C)
	<b>Operating relative humidity</b>	5% to 95%, noncondensing
	<b>Nonoperating/Storage temperature</b>	-40°F to 158°F (-40°C to 70°C)
	<b>Nonoperating/Storage relative humidity</b>	5% to 95%, noncondensing
<b>Electrical characteristics</b>	<b>Voltage</b>	100-120/200-240 VAC
	<b>DC Voltage</b>	-48 V/-60 V
	<b>Current</b>	16/92 A
	<b>Power output</b>	3500 W
	<b>Frequency</b>	50/60 Hz
	<b>Notes</b>	Based on a 3500 W DC power supply
<b>Safety</b>	UL 60950-1; IEC 60950-1; CAN/CSA-C22.2 No. 60950-1; EN 60950-1/A11	

### Technical Specifications

<b>Emissions</b>	VCCI Class A; EN 55022 Class A; ICES-003 Class A; ANSI C63.4 2003; AS/NZS CISPR22 Class A; EN 61000-3-2:2006; EN 61000-3-3:1995 +A1:2001+A2:2005; EMC Directive 2004/108/EC; FCC (CFR 47, Part 15) Class A
<b>Immunity</b>	<p><b>Generic</b> ETSI EN 300 386 V1.3.3</p> <p><b>EN</b> EN 61000-4-2:1995+A1:1998+A2:2001</p> <p><b>ESD</b> EN 61000-4-2</p> <p><b>Radiated</b> EN 61000-4-3</p> <p><b>EFT/Burst</b> EN 61000-4-4</p> <p><b>Surge</b> EN 61000-4-5</p> <p><b>Conducted</b> EN 61000-4-6</p> <p><b>Power frequency magnetic field</b> IEC 61000-4-8</p> <p><b>Voltage dips and interruptions</b> EN 61000-4-11</p> <p><b>Harmonics</b> EN 61000-3-2, IEC 61000-3-2</p> <p><b>Flicker</b> EN 61000-3-3, IEC 61000-3-3</p>
<b>Management</b>	IMC - Intelligent Management Center; command-line interface; out-of-band management (serial RS-232C); SNMP Manager; Telnet; terminal interface (serial RS-232C); modem interface; IEEE 802.3 Ethernet MIB; Ethernet Interface MIB
<b>Notes</b>	IPSec/IKE functionality provided by HP 9500 VPN/Firewall Module (JD245A)
<b>Services</b>	<p>3-year, parts only, global next-day advance exchange (UX016E)</p> <p>3-year, 4-hour onsite, 13x5 coverage for hardware (UX017E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware (UX020E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 SW phone support and SW updates (UX023E)</p> <p>3-year, 24x7 SW phone support, software updates (UX026E)</p> <p>Installation with minimum configuration, system-based pricing (UX033E)</p> <p>4-year, 4-hour onsite, 13x5 coverage for hardware (UX018E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware (UX021E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UX024E)</p> <p>4-year, 24x7 SW phone support, software updates (UX027E)</p> <p>5-year, 4-hour onsite, 13x5 coverage for hardware (UX019E)</p> <p>5-year, 4-hour onsite, 24x7 coverage for hardware (UX022E)</p> <p>5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UX025E)</p> <p>5-year, 24x7 SW phone support, software updates (UX028E)</p> <p>3 Yr 6 hr Call-to-Repair Onsite (UX029E)</p> <p>4 Yr 6 hr Call-to-Repair Onsite (UX030E)</p> <p>5 Yr 6 hr Call-to-Repair Onsite (UX031E)</p> <p>1-year, post-warranty, 4-hour onsite, 13x5 coverage for hardware (HR504E)</p> <p>1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware (HR505E)</p> <p>1-year, 6 hour Call-To-Repair Onsite for hardware (HR508E)</p> <p>1-year, 24x7 software phone support, software updates (HR507E)</p> <p>1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (HR506E)</p>

Refer to the HP website at: [www.hp.com/networking/services](http://www.hp.com/networking/services) for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

### Technical Specifications

#### HP 9505 Switch Chassis (JC124B)

<b>Included accessories</b>	1 HP 9512/9505/8812/8805 Spare Fan Assembly (JC109A)	
<b>Ports</b>	2 switch fabric slots 5 I/O module slots Supports a maximum of 80 10-GbE ports or 240 autosensing 10/100/1000 ports or 240 SFP ports, with optional module	
<b>Power supplies</b>	2 power supply slots 1 minimum power supply required (ordered separately)	
<b>Fan tray</b>	includes: 1 x JC109A 1 fan tray slot	
<b>Physical characteristics</b>	<b>Dimensions</b>	17.4(w) x 17.72(d) x 19.13(h) in (44.2 x 45.0 x 48.6 cm) (11U height)
	<b>Weight</b>	88.18 lb. (40 kg), Fully loaded chassis, two fabrics, two power supplies, and a full complement of typical I/O modules
	<b>Full configuration weight</b>	154.32 lb. (70 kg)
<b>Memory and processor</b>	<b>Fabric</b>	PowerPC @ 1000 MHz, 128 MB flash, 1 GB RAM, 256 MB compact flash
	<b>I/O Module</b>	PowerPC @ 667 MHz, 512 MB RAM
<b>Mounting</b>	Mounts in an EIA standard 19-in. rack or other equipment cabinet (hardware included); horizontal surface mounting only	
<b>Performance</b>	<b>1000 Mb Latency</b>	< 6.0 $\mu$ s (FIFO 64-byte packets)
	<b>10 Gbps Latency</b>	< 6.0 $\mu$ s (FIFO 64-byte packets)
	<b>Throughput</b>	357 million pps
	<b>Routing/Switching capacity</b>	600 Gbps
	<b>Routing table size</b>	256000 entries
	<b>Availability</b>	99.999%
<b>Reliability</b>	<b>Operating temperature</b>	32°F to 113°F (0°C to 45°C)
	<b>Operating relative humidity</b>	5% to 95%, noncondensing
	<b>Nonoperating/Storage temperature</b>	-40°F to 158°F (-40°C to 70°C)
	<b>Nonoperating/Storage relative humidity</b>	5% to 95%, noncondensing
<b>Electrical characteristics</b>	<b>Voltage</b>	100-120/200-240 VAC
	<b>DC Voltage</b>	-48 V/-60 V
	<b>Current</b>	16/92 A
	<b>Power output</b>	3500 W
	<b>Frequency</b>	50/60 Hz
	<b>Notes</b>	Based on a 3500 W DC power supply
<b>Safety</b>	UL 60950-1; IEC 60950-1; CAN/CSA-C22.2 No. 60950-1; EN 60950-1/A11	

### Technical Specifications

<b>Emissions</b>	VCCI Class A; EN 55022 Class A; ICES-003 Class A; ANSI C63.4 2003; AS/NZS CISPR22 Class A; EN 61000-3-2:2006; EN 61000-3-3:1995 +A1:2001+A2:2005; EMC Directive 2004/108/EC; FCC (CFR 47, Part 15) Class A																						
<b>Immunity</b>	<table border="0"> <tr> <td style="vertical-align: top;"><b>Generic</b></td> <td>ETSI EN 300 386 V1.3.3</td> </tr> <tr> <td style="vertical-align: top;"><b>EN</b></td> <td>EN 61000-4-2:1995+A1:1998+A2:2001</td> </tr> <tr> <td style="vertical-align: top;"><b>ESD</b></td> <td>EN 61000-4-2</td> </tr> <tr> <td style="vertical-align: top;"><b>Radiated</b></td> <td>EN 61000-4-3</td> </tr> <tr> <td style="vertical-align: top;"><b>EFT/Burst</b></td> <td>EN 61000-4-4</td> </tr> <tr> <td style="vertical-align: top;"><b>Surge</b></td> <td>EN 61000-4-5</td> </tr> <tr> <td style="vertical-align: top;"><b>Conducted</b></td> <td>EN 61000-4-6</td> </tr> <tr> <td style="vertical-align: top;"><b>Power frequency magnetic field</b></td> <td>IEC 61000-4-8</td> </tr> <tr> <td style="vertical-align: top;"><b>Voltage dips and interruptions</b></td> <td>EN 61000-4-11</td> </tr> <tr> <td style="vertical-align: top;"><b>Harmonics</b></td> <td>EN 61000-3-2, IEC 61000-3-2</td> </tr> <tr> <td style="vertical-align: top;"><b>Flicker</b></td> <td>EN 61000-3-3, IEC 61000-3-3</td> </tr> </table>	<b>Generic</b>	ETSI EN 300 386 V1.3.3	<b>EN</b>	EN 61000-4-2:1995+A1:1998+A2:2001	<b>ESD</b>	EN 61000-4-2	<b>Radiated</b>	EN 61000-4-3	<b>EFT/Burst</b>	EN 61000-4-4	<b>Surge</b>	EN 61000-4-5	<b>Conducted</b>	EN 61000-4-6	<b>Power frequency magnetic field</b>	IEC 61000-4-8	<b>Voltage dips and interruptions</b>	EN 61000-4-11	<b>Harmonics</b>	EN 61000-3-2, IEC 61000-3-2	<b>Flicker</b>	EN 61000-3-3, IEC 61000-3-3
<b>Generic</b>	ETSI EN 300 386 V1.3.3																						
<b>EN</b>	EN 61000-4-2:1995+A1:1998+A2:2001																						
<b>ESD</b>	EN 61000-4-2																						
<b>Radiated</b>	EN 61000-4-3																						
<b>EFT/Burst</b>	EN 61000-4-4																						
<b>Surge</b>	EN 61000-4-5																						
<b>Conducted</b>	EN 61000-4-6																						
<b>Power frequency magnetic field</b>	IEC 61000-4-8																						
<b>Voltage dips and interruptions</b>	EN 61000-4-11																						
<b>Harmonics</b>	EN 61000-3-2, IEC 61000-3-2																						
<b>Flicker</b>	EN 61000-3-3, IEC 61000-3-3																						
<b>Management</b>	IMC - Intelligent Management Center; command-line interface; out-of-band management (serial RS-232C); SNMP Manager; Telnet; terminal interface (serial RS-232C); modem interface; IEEE 802.3 Ethernet MIB; Ethernet Interface MIB																						
<b>Notes</b>	IPSec/IKE functionality provided by HP 9500 VPN/Firewall Module (JD245A)																						
<b>Services</b>	<p>3-year, parts only, global next-day advance exchange (UX016E)</p> <p>3-year, 4-hour onsite, 13x5 coverage for hardware (UX017E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware (UX020E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 SW phone support and SW updates (UX023E)</p> <p>3-year, 24x7 SW phone support, software updates (UX026E)</p> <p>Installation with minimum configuration, system-based pricing (UX033E)</p> <p>4-year, 4-hour onsite, 13x5 coverage for hardware (UX018E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware (UX021E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UX024E)</p> <p>4-year, 24x7 SW phone support, software updates (UX027E)</p> <p>5-year, 4-hour onsite, 13x5 coverage for hardware (UX019E)</p> <p>5-year, 4-hour onsite, 24x7 coverage for hardware (UX022E)</p> <p>5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UX025E)</p> <p>5-year, 24x7 SW phone support, software updates (UX028E)</p> <p>3 Yr 6 hr Call-to-Repair Onsite (UX029E)</p> <p>4 Yr 6 hr Call-to-Repair Onsite (UX030E)</p> <p>5 Yr 6 hr Call-to-Repair Onsite (UX031E)</p> <p>1-year, post-warranty, 4-hour onsite, 13x5 coverage for hardware (HR504E)</p> <p>1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware (HR505E)</p> <p>1-year, 6 hour Call-To-Repair Onsite for hardware (HR508E)</p> <p>1-year, 24x7 software phone support, software updates (HR507E)</p> <p>1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (HR506E)</p>																						

Refer to the HP website at: [www.hp.com/networking/services](http://www.hp.com/networking/services) for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

### Technical Specifications

#### Standards and protocols

(applies to all products in series)

#### BGP

RFC 1771 BGPv4  
RFC 1772 Application of the BGP  
RFC 1965 BGP4 confederations  
RFC 1997 BGP Communities Attribute  
RFC 1998 PPP Gandalf FZA Compression Protocol  
RFC 2385 BGP Session Protection via TCP MD5  
RFC 2439 BGP Route Flap Damping  
RFC 2547 BGP/MPLS VPNs  
RFC 2796 BGP Route Reflection  
RFC 2858 BGP-4 Multi-Protocol Extensions  
RFC 2918 Route Refresh Capability  
RFC 3065 Autonomous System Confederations for BGP  
RFC 3107 Support BGP carry Label for MPLS  
RFC 3392 Capabilities Advertisement with BGP-4  
RFC 4271 A Border Gateway Protocol 4 (BGP-4)  
RFC 4272 BGP Security Vulnerabilities Analysis  
RFC 4273 Definitions of Managed Objects for BGP-4  
RFC 4274 BGP-4 Protocol Analysis  
RFC 4275 BGP-4 MIB Implementation Survey  
RFC 4276 BGP-4 Implementation Report  
RFC 4277 Experience with the BGP-4 Protocol  
RFC 4360 BGP Extended Communities Attribute  
RFC 4456 BGP Route Reflection: An Alternative to Full Mesh Internal BGP (IBGP)  
RFC 4724 Graceful Restart Mechanism for BGP  
RFC 4760 Multiprotocol Extensions for BGP-4

#### Denial of service protection

RFC 2267 Network Ingress Filtering  
Automatic filtering of well-known denial-of-service packets  
CPU DoS Protection  
Rate Limiting by ACLs

#### Device management

RFC 1157 SNMPv1/v2c  
RFC 1305 NTPv3  
RFC 1902 (SNMPv2)  
RFC 2271 FrameWork  
RFC 2579 (SMIv2 Text Conventions)  
RFC 2580 (SMIv2 Conformance)  
RFC 2819 (RMON groups Alarm, Event, History and Statistics only)  
Multiple Configuration Files  
Multiple Software Images  
SSHv1/SSHv2 Secure Shell  
TACACS/TACACS+

#### MIBs

RFC 1156 (TCP/IP MIB)  
RFC 1157 A Simple Network Management Protocol (SNMP)  
RFC 1213 MIB II  
RFC 1215 A Convention for Defining Traps for use with the SNMP  
RFC 1229 Interface MIB Extensions  
RFC 1271 Remote Network Monitoring Management Information Base  
RFC 1493 Bridge MIB  
RFC 1643 Ethernet MIB  
RFC 1657 BGP-4 MIB  
RFC 1724 RIPv2 MIB  
RFC 1757 Remote Network Monitoring MIB  
RFC 1850 OSPFv2 MIB  
RFC 2012 SNMPv2 MIB for TCP  
RFC 2013 SNMPv2 MIB for UDP  
RFC 2021 RMONv2 MIB  
RFC 2096 IP Forwarding Table MIB  
RFC 2127 ISDN Management Information Base using SMIv2  
RFC 2233 Interfaces MIB  
RFC 2268 Definitions of Managed Objects for IEEE 802.3 Medium Attachment Units (MAUs)  
RFC 2452 IPV6-TCP-MIB  
RFC 2454 IPV6-UDP-MIB  
RFC 2465 IPV6 MIB  
RFC 2466 ICMPv6 MIB  
RFC 2571 SNMP Framework MIB  
RFC 2572 SNMP-MPD MIB  
RFC 2573 SNMP-Target MIB  
RFC 2578 Structure of Management Information Version 2 (SMIv2)  
RFC 2579 Textual Conventions for SMIv2  
RFC 2580 Conformance Statements for SMIv2  
RFC 2613 SMON MIB  
RFC 2618 RADIUS Client MIB  
RFC 2620 RADIUS Accounting MIB  
RFC 2665 Ethernet-Like-MIB  
RFC 2674 802.1p and IEEE 802.1Q Bridge MIB  
RFC 2787 VRRP MIB  
RFC 2819 RMON MIB  
RFC 2856 Textual Conventions for Additional High Capacity Data Types  
RFC 2863 The Interfaces Group MIB  
RFC 2925 Ping MIB  
RFC 2932IP (Multicast Routing MIB)  
RFC 2933 IGMP MIB  
RFC 2934 Protocol Independent Multicast MIB for

### Technical Specifications

#### General protocols

IEEE 802.1ad Q-in-Q  
IEEE 802.1p Priority  
IEEE 802.1Q VLANs  
IEEE 802.1s Multiple Spanning Trees  
IEEE 802.1w Rapid Reconfiguration of Spanning Tree  
IEEE 802.1X PAE  
IEEE 802.3ab 1000BASE-T  
IEEE 802.3ac (VLAN Tagging Extension)  
IEEE 802.3ad Link Aggregation Control Protocol (LACP)  
IEEE 802.3ae 10-Gigabit Ethernet  
IEEE 802.3ah Ethernet in First Mile over Point to Point Fiber - EFMF  
IEEE 802.3u 100BASE-X  
IEEE 802.3x Flow Control  
IEEE 802.3z 1000BASE-X  
RFC 768 UDP  
RFC 783 TFTP Protocol (revision 2)  
RFC 791 IP  
RFC 792 ICMP  
RFC 793 TCP  
RFC 826 ARP  
RFC 854 TELNET  
RFC 894 IP over Ethernet  
RFC 903 RARP  
RFC 906 TFTP Bootstrap  
RFC 925 Multi-LAN Address Resolution  
RFC 950 Internet Standard Subnetting Procedure  
RFC 951 BOOTP  
RFC 959 File Transfer Protocol (FTP)  
RFC 1027 Proxy ARP  
RFC 1042 IP Datagrams  
RFC 1058 RIPv1  
RFC 1142 OSI IS-IS Intra-domain Routing Protocol  
RFC 1195 OSI ISIS for IP and Dual Environments  
RFC 1213 Management Information Base for Network Management of TCP/IP-based internets  
RFC 1256 ICMP Router Discovery Protocol (IRDP)  
RFC 1293 Inverse Address Resolution Protocol  
RFC 1305 NTPv3  
RFC 1350 TFTP Protocol (revision 2)  
RFC 1519 CIDR  
RFC 1531 Dynamic Host Configuration Protocol  
RFC 1533 DHCP Options and BOOTP Vendor Extensions  
RFC 1541 DHCP  
RFC 1591 DNS (client only)

#### IPv4

RFC 3273 HC-RMON MIB  
RFC 3414 SNMP-User based-SM MIB  
RFC 3415 SNMP-View based-ACM MIB  
RFC 3417 Simple Network Management Protocol (SNMP) over IEEE 802 Networks  
RFC 3418 MIB for SNMPv3  
RFC 3593 Textual Conventions for MIB Modules Using Performance History Based on 15 Minute Intervals  
RFC 3595 Textual Conventions for IPv6 Flow Label  
RFC 3621 Power Ethernet MIB  
RFC 3811 Definitions of Textual Conventions (TCs) for Multiprotocol Label Switching (MPLS) Management  
RFC 3812 Multiprotocol Label Switching (MPLS) Traffic Engineering (TE) Management Information Base (MIB)  
RFC 3813 MPLS LSR MIB  
RFC 3814 MPLS FTN MIB  
RFC 3815 MPLS LDP MIB  
RFC 3826 AES for SNMP's USM MIB  
RFC 4113 UDP MIB  
RFC 4444 Management Information Base for Intermediate System to Intermediate System (IS-IS)

#### MPLS

RFC 2205 Resource ReSerVation Protocol (RSVP) - Version 1 Functional Specification  
RFC 2209 Resource ReSerVation Protocol (RSVP)  
RFC 2702 Requirements for Traffic Engineering Over MPLS  
RFC 2858 Multiprotocol Extensions for BGP-4  
RFC 3031 Multiprotocol Label Switching Architecture  
RFC 3032 MPLS Label Stack Encoding  
RFC 3107 Carrying Label Information in BGP-4  
RFC 3479 Fault Tolerance for the Label Distribution Protocol (LDP)  
RFC 3487 Graceful Restart Mechanism for LDP  
RFC 4090 Fast Reroute Extensions to RSVP-TE for LSP Tunnels  
RFC 4364 BGP/MPLS IP Virtual Private Networks (VPNs)  
RFC 4379 Detecting Multi-Protocol Label Switched (MPLS) Data Plane Failures  
RFC 4447 Pseudowire Setup and Maintenance Using LDP  
RFC 4448 Encapsulation Methods for Transport of Ethernet over MPLS Networks

### Technical Specifications

RFC 1631 NAT  
RFC 1701 Generic Routing Encapsulation  
RFC 1721 RIP-2 Analysis  
RFC 1723 RIP v2  
RFC 1812 IPv4 Routing  
RFC 2030 Simple Network Time Protocol (SNTP) v4  
RFC 2131 DHCP  
RFC 2138 Remote Authentication Dial In User Service (RADIUS)  
RFC 2338 VRRP  
RFC 2453 RIPv2  
RFC 2644 Directed Broadcast Control  
RFC 2763 Dynamic Name-to-System ID mapping support  
RFC 2784 Generic Routing Encapsulation (GRE)  
RFC 2865 Remote Authentication Dial In User Service (RADIUS)  
RFC 2966 Domain-wide Prefix Distribution with Two-Level IS-IS  
RFC 2973 IS-IS Mesh Groups  
RFC 3022 Traditional IP Network Address Translator (Traditional NAT)  
RFC 3277 IS-IS Transient Blackhole Avoidance  
RFC 3567 Intermediate System to Intermediate System (IS-IS) Cryptographic Authentication  
RFC 3619 Ethernet Automatic Protection Switching (EAPS)  
RFC 3719 Recommendations for Interoperable Networks using Intermediate System to Intermediate System (IS-IS)  
RFC 3784 ISIS TE support  
RFC 3786 Extending the Number of IS-IS LSP Fragments Beyond the 256 Limit  
RFC 3787 Recommendations for Interoperable IP Networks using Intermediate System to Intermediate System (IS-IS)  
RFC 3847 Restart signaling for IS-IS  
RFC 4251 The Secure Shell (SSH) Protocol Architecture  
RFC 5130 A Policy Control Mechanism in IS-IS Using Administrative Tags

#### **IP multicast**

RFC 2236 IGMPv2  
RFC 2710 Multicast Listener Discovery (MLD) for IPv6  
RFC 3376 IGMPv3  
RFC 3446 Anycast Rendezvous Point (RP)

RFC 4664 Framework for Layer 2 Virtual Private Networks  
RFC 4665 Service Requirements for Layer 2 Provider Provisioned Virtual Private Networks  
RFC 4761 Virtual Private LAN Service (VPLS) Using BGP for Auto-Discovery and Signaling  
RFC 4762 Virtual Private LAN Service (VPLS) Using Label Distribution Protocol (LDP) Signaling  
RFC 5036 LDP Specification

#### **Network management**

IEEE 802.1AB Link Layer Discovery Protocol (LLDP)  
RFC 1155 Structure of Management Information  
RFC 1157 SNMPv1  
RFC 1448 Protocol Operations for version 2 of the Simple Network Management Protocol (SNMPv2)  
RFC 2211 Controlled-Load Network  
RFC 2819 Four groups of RMON: 1 (statistics), 2 (history), 3 (alarm) and 9 (events)  
RFC 3164 BSD syslog Protocol  
RFC 3176 sFlow  
RFC 3411 SNMP Management Frameworks  
RFC 3414 SNMPv3 User-based Security Model (USM)  
RFC 3415 SNMPv3 View-based Access Control Model VACM)

#### **OSPF**

RFC 1245 OSPF protocol analysis  
RFC 1246 Experience with OSPF  
RFC 1765 OSPF Database Overflow  
RFC 1850 OSPFv2 Management Information Base (MIB), traps  
RFC 2328 OSPFv2  
RFC 2370 OSPF Opaque LSA Option  
RFC 3101 OSPF NSSA  
RFC 3137 OSPF Stub Router Advertisement  
RFC 3623 Graceful OSPF Restart  
RFC 3630 Traffic Engineering Extensions to OSPF Version 2  
RFC 4061 Benchmarking Basic OSPF Single Router Control Plane Convergence  
RFC 4062 OSPF Benchmarking Terminology and Concepts  
RFC 4063 Considerations When Using Basic OSPF Convergence Benchmarks  
RFC 4222 Prioritized Treatment of Specific OSPF Version 2 Packets and Congestion Avoidance  
RFC 4577 OSPF as the Provider/Customer Edge Protocol for BGP/MPLS IP Virtual Private Networks

### Technical Specifications

mechanism using Protocol Independent Multicast (PIM) and Multicast Source Discovery Protocol (MSDP)  
RFC 3618 Multicast Source Discovery Protocol (MSDP)  
RFC 3973 PIM Dense Mode  
RFC 4601 Draft 10 PIM Sparse Mode  
RFC 4604 Using Internet Group Management Protocol Version 3 (IGMPv3) and Multicast Listener Discovery Protocol Version 2 (MLDv2) for Source-Specific Multicast  
RFC 4605 IGMP/MLD Proxying  
RFC 4607 Source-Specific Multicast for IP  
RFC 4610 Anycast-RP Using Protocol Independent Multicast (PIM)  
RFC 5059 Bootstrap Router (BSR) Mechanism for Protocol Independent Multicast (PIM)  
draft-rosen-vpn-mcast-08

#### IPv6

RFC 1886 DNS Extension for IPv6  
RFC 1887 IPv6 Unicast Address Allocation Architecture  
RFC 1981 IPv6 Path MTU Discovery  
RFC 2080 RIPng for IPv6  
RFC 2081 RIPng Protocol Applicability Statement  
RFC 2292 Advanced Sockets API for IPv6  
RFC 2373 IPv6 Addressing Architecture  
RFC 2375 IPv6 Multicast Address Assignments  
RFC 2460 IPv6 Specification  
RFC 2461 IPv6 Neighbor Discovery  
RFC 2462 IPv6 Stateless Address Auto-configuration  
RFC 2463 ICMPv6  
RFC 2464 Transmission of IPv6 over Ethernet Networks  
RFC 2473 Generic Packet Tunneling in IPv6  
RFC 2526 Reserved IPv6 Subnet Anycast Addresses  
RFC 2529 Transmission of IPv6 Packets over IPv4  
RFC 2545 Use of MP-BGP-4 for IPv6  
RFC 2553 Basic Socket Interface Extensions for IPv6  
RFC 2710 Multicast Listener Discovery (MLD) for IPv6  
RFC 2740 OSPFv3 for IPv6  
RFC 2767 Dual stacks IPv4 & IPv6  
RFC 2893 Transition Mechanisms for IPv6 Hosts and Routers  
RFC 3056 Connection of IPv6 Domains via IPv4 Clouds  
RFC 3307 IPv6 Multicast Address Allocation  
RFC 3315 DHCPv6 (client and relay)

(VPNs)  
RFC 4811 OSPF Out-of-Band LSDB Resynchronization  
RFC 4812 OSPF Restart Signaling  
RFC 4813 OSPF Link-Local Signaling  
RFC 4940 IANA Considerations for OSPF

#### QoS/CoS

IEEE 802.1P (CoS)  
RFC 1349 Type of Service in the Internet Protocol Suite  
RFC 2211 Specification of the Controlled-Load Network Element Service  
RFC 2212 Guaranteed Quality of Service  
RFC 2474 DSCP DiffServ  
RFC 2475 DiffServ Architecture  
RFC 2597 DiffServ Assured Forwarding (AF)  
RFC 2598 DiffServ Expedited Forwarding (EF)  
RFC 2697 A Single Rate Three Color Marker  
RFC 2698 A Two Rate Three Color Marker

#### Security

IEEE 802.1X Port Based Network Access Control  
RFC 1321 The MD5 Message-Digest Algorithm  
RFC 1334 PPP Authentication Protocols (PAP)  
RFC 1492 An Access Control Protocol, Sometimes Called TACACS  
RFC 1492 TACACS+  
RFC 1994 PPP Challenge Handshake Authentication Protocol (CHAP)  
RFC 2082 RIP-2 MD5 Authentication  
RFC 2104 Keyed-Hashing for Message Authentication  
RFC 2138 RADIUS Authentication  
RFC 2408 Internet Security Association and Key Management Protocol (ISAKMP)  
RFC 2409 The Internet Key Exchange (IKE)  
RFC 2716 PPP EAP TLS Authentication Protocol  
RFC 2865 RADIUS Authentication  
RFC 2866 RADIUS Accounting  
RFC 2867 RADIUS Accounting Modifications for Tunnel Protocol Support  
RFC 2868 RADIUS Attributes for Tunnel Protocol Support  
RFC 2869 RADIUS Extensions  
Access Control Lists (ACLs)  
Guest VLAN for 802.1x  
MAC Authentication  
Secure Sockets Layer (SSL)  
SSHv1/SSHv2 Secure Shell

### Technical Specifications

RFC 3484 Default Address Selection for IPv6  
RFC 3513 IPv6 Addressing Architecture  
RFC 3587 IPv6 Global Unicast Address Format  
RFC 3736 Stateless Dynamic Host Configuration Protocol (DHCP) Service for IPv6  
RFC 3810 MLDv2 for IPv6  
RFC 4007 IPv6 Scoped Address Architecture  
RFC 4214 Intra-Site Automatic Tunnel Addressing Protocol (ISATAP)  
RFC 4291 IP Version 6 Addressing Architecture  
RFC 4293 MIB for IP  
RFC 4862 IPv6 Stateless Address Auto-configuration  
RFC 4940 IANA Considerations for OSPF  
RFC 5178 OSPFv3 Graceful Restart

#### **VPN**

RFC 2403 - HMAC-MD5-96  
RFC 2404 - HMAC-SHA1-96  
RFC 2405 - DES-CBC Cipher algorithm  
RFC 2407 - Domain of interpretation  
RFC 2547 BGP/MPLS VPNs

#### **IPsec**

RFC 1828 IP Authentication using Keyed MD5  
RFC 1829 The ESP DES-CBC Transform  
RFC 2085 HMAC-MD5 IP Authentication with Replay Prevention  
RFC 2401 IP Security Architecture  
RFC 2402 IP Authentication Header  
RFC 2406 IP Encapsulating Security Payload  
RFC 2410 - The NULL Encryption Algorithm and its use with IPsec  
RFC 2411 IP Security Document Roadmap  
RFC 2451 The ESP CBC-Mode Cipher Algorithms  
RFC 3602 The AES-CBC Cipher Algorithm and Its Use with IPsec

### Accessories

<b>HP 9500 Switch Series accessories</b>	<b>Modules</b>	
	HP 9500 48-port GbE SFP LEB Module	JC113/
	HP 9500 48-port Gig-T LEB Module	JC107/
	HP 9500 48-port Gig-T	JC116/
	HP 9500 16-port GbE SFP/8-port GbE Combo LEB Module	JC123/
	HP 9500 16-port Gig-T/8-port GbE Combo LEB Module	JC122/
	HP 9500 16-port 10-GbE SFP+ REB Module	JC108/
	HP 9500 4-port 10-GbE XFP LEB Module	JC114/
	HP 9500 2-port 10-GbE XFP LEB Module	JC112/
	HP 9500 48-port GbE SFP LEC Module	JC471/
	HP 9500 48-port Gig-T LEC Module	JC115/
	HP 9500 16-port GbE SFP/8-port GbE Combo LEC Module	JC117/
	HP 9500 16-port Gig-T/8-port GbE Combo LEC Module	JC119/
	HP 9500 4-port 10-GbE XFP LEC Module	JC118/
	HP 9500 2-port 10-GbE XFP LEC Module	JC470/
	<b>Transceivers</b>	
	HP X114 100M SFP LC FX Transceiver	JF833/
	HP X120 100M/1G SFP LC LX Transceiver	JF832/
	HP X125 1G SFP RJ45 T Transceiver	JD089E
	HP X120 1G SFP LC SX Transceiver	JD118E
	HP X120 1G SFP LC LX Transceiver	JD119E
	HP X124 1G SFP LC LH40 1310nm Transceiver	JD061/
	HP X120 1G SFP LC LH40 1550nm Transceiver	JD062/
	HP X125 1G SFP LC LH70 Transceiver	JD063E
	HP X120 1G SFP LC LH100 Transceiver	JD103/
	HP X120 1G SFP LC BX 10-U Transceiver	JD098E
	HP X120 1G SFP LC BX 10-D Transceiver	JD099E
	HP X130 10G XFP LC SR Transceiver	JD117E
	HP X130 10G XFP LC LR Transceiver	JD108E
	HP X135 10G XFP LC ER Transceiver	JD121/
	HP X130 10G XFP LC ZR Transceiver	JD107/
	HP X130 SFP+ LC SR Transceiver	JD092E
	HP X130 SFP+ LC LRM Transceiver	JD093E
	HP X130 SFP+ LC LR Transceiver	JD094E
	HP X170 1G SFP LC LH70 1470 Transceiver	JD113/
	HP X170 1G SFP LC LH70 1490 Transceiver	JD114/
	HP X170 1G SFP LC LH70 1510 Transceiver	JD115/
	HP X170 1G SFP LC LH70 1530 Transceiver	JD116/
	HP X170 1G SFP LC LH70 1550 Transceiver	JD109/
	HP X170 1G SFP LC LH70 1570 Transceiver	JD110/
HP X170 1G SFP LC LH70 1590 Transceiver	JD111/	
HP X170 1G SFP LC LH70 1610 Transceiver	JD112/	
HP X240 10G SFP+ to SFP+ 3m Direct Attach Copper Cable	JD097/	
HP X240 10G SFP+ to SFP+ 5m Direct Attach Copper Cable	JG081/	

### Accessories

#### Cables

HP 50 m Multimode OM3 LC/LC Optical Cable	AJ839/
HP 30 m Multimode OM3 LC/LC Optical Cable	AJ838/
HP 15 m Multimode OM3 LC/LC Optical Cable	AJ837/
HP 5 m Multimode OM3 LC/LC Optical Cable	AJ836/
HP 2 m Multimode OM3 LC/LC Optical Cable	AJ835/
HP 1 m Multimode OM3 LC/LC Optical Cable	AJ834/
HP 0.5 m Multimode OM3 LC/LC Optical Cable	AJ833/
HP Premier Flex LC/LC Multi-mode OM4 2 fiber 1m Cable	QK732/
HP Premier Flex LC/LC Multi-mode OM4 2 fiber 2m Cable	QK733/
HP Premier Flex LC/LC Multi-mode OM4 2 fiber 5m Cable	QK734/
HP Premier Flex LC/LC Multi-mode OM4 2 fiber 15m Cable	QK735/
HP Premier Flex LC/LC Multi-mode OM4 2 fiber 30m Cable	QK736/
HP Premier Flex LC/LC Multi-mode OM4 2 fiber 50m Cable	QK737/

#### Power Supply

HP 9500 3500W AC Power Frame	JC111/
HP 9500/8800 3500W DC Power Supply	JC473/
HP 9500/8800 1800W AC Power Supply	JC110/
HP 9500/8800 2000W DC Power Supply	JC029/

#### License

HP WX Blade 128 AP License Upgrade	JD464/
------------------------------------	--------

#### WLAN

HP 9500 Access Controller Module	JD442/
----------------------------------	--------

#### Appliance

HP 9500 VPN Firewall Module	JD245/
HP 9500 Load Balancing Module	JD247/
HP 9500 NetStream Monitoring Module	JD246/

#### Memory

HP 12500 additional 1 GB SDRAM DDR2	JC071/
-------------------------------------	--------

#### HP 9512 Switch Chassis (JC125B)

HP 9500 720Gbps Fabric Module	JC120/
HP 9512/9505/8800 Spare Fan Assembly	JC109/

#### HP 9508-V Switch Chassis (JC474B)

HP 9500 720Gbps Fabric/Main Processing Unit	JC120/
HP 9508-V Fan Assembly	JC475/

#### HP 9505 Switch Chassis (JC124B)

HP 9505 360Gbps Fabric/Main Processing Unit	JC121/
HP 9512/9505/8800 Spare Fan Assembly	JC109/

### Accessory Product Details

**NOTE:** Details are not available for all accessories. The following specifications were available at the time of publication.

<b>HP 9500 48-port GbE SFP Module (JC113A)</b>	<b>Ports</b>	48 SFP 100/1000 Mbps ports	
	<b>Physical characteristics</b>	Dimensions	14.96(d) x 15.75(w) x 1.57(h) in. (38 x 40 x 4 cm)
		Weight	7.47 lb. (3.39 kg)
<b>Services</b>	Refer to the HP website at <a href="http://www.hp.com/networking/services">www.hp.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.		
<b>HP 9500 48-port Gig-T Module (JC107A)</b>	<b>Ports</b>	48 RJ-45 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only	
	<b>Physical characteristics</b>	Dimensions	14.96(d) x 15.75(w) x 1.57(h) in. (38 x 40 x 4 cm)
		Weight	7.1 lb. (3.22 kg)
<b>Services</b>	Refer to the HP website at <a href="http://www.hp.com/networking/services">www.hp.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.		
<b>HP 9500 48-port Gig-T 2.4:1 Module (JC116A)</b>	<b>Physical characteristics</b>	Dimensions	14.96(d) x 15.75(w) x 1.57(h) in. (38 x 40 x 4 cm)
		Weight	7.32 lb. (3.32 kg)
	<b>Services</b>	Refer to the HP website at <a href="http://www.hp.com/networking/services">www.hp.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.	
<b>HP 9500 24-port GbE SFP Module (JC123A)</b>	<b>Ports</b>	16 SFP 100/1000 Mbps ports 8 dual-personality ports; 1000M Combo ports (SFP or RJ-45)	
	<b>Physical characteristics</b>	Dimensions	14.96(d) x 15.75(w) x 1.57(h) in. (38 x 40 x 4 cm)
		Weight	6.77 lb. (3.07 kg)
<b>Services</b>	Refer to the HP website at <a href="http://www.hp.com/networking/services">www.hp.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.		

### Accessory Product Details

<b>HP 9500 24-port Gig-T Module (JC122A)</b>	<b>Ports</b>	16 RJ-45 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only 8 dual-personality ports; 1000M Combo ports (SFP or RJ-45)	
	<b>Physical characteristics</b>	<b>Dimensions</b>	14.96(d) x 15.75(w) x 1.57(h) in. (38 x 40 x 4 cm)
		<b>Weight</b>	6.66 lb. (3.02 kg)
	<b>Services</b>	Refer to the HP website at <a href="http://www.hp.com/networking/services">www.hp.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.	
<hr/>			
<b>HP 9500 16-port 10GbE SFP+ Module (JC108A)</b>	<b>Ports</b>	16 SFP+ 10-GbE ports; Duplex: full only	
	<b>Physical characteristics</b>	<b>Dimensions</b>	14.96(d) x 15.75(w) x 1.57(h) in. (38 x 40 x 4 cm)
		<b>Weight</b>	7.32 lb. (3.32 kg)
	<b>Services</b>	Refer to the HP website at <a href="http://www.hp.com/networking/services">www.hp.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.	
<hr/>			
<b>HP 9500 4-port 10GbE XFP Module (JC114A)</b>	<b>Ports</b>	4 XFP 10-GbE ports; Duplex: full only	
	<b>Physical characteristics</b>	<b>Dimensions</b>	14.96(d) x 15.75(w) x 1.57(h) in. (38 x 40 x 4 cm)
		<b>Weight</b>	6.79 lb. (3.08 kg)
	<b>Services</b>	Refer to the HP website at <a href="http://www.hp.com/networking/services">www.hp.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.	
<hr/>			
<b>HP 9500 2-port 10GbE XFP Module (JC112A)</b>	<b>Ports</b>	2 XFP 10-GbE ports; Duplex: full only	
	<b>Physical characteristics</b>	<b>Dimensions</b>	14.96(d) x 15.75(w) x 1.57(h) in. (38 x 40 x 4 cm)
		<b>Weight</b>	6.48 lb. (2.94 kg)
	<b>Services</b>	Refer to the HP website at <a href="http://www.hp.com/networking/services">www.hp.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.	

### Accessory Product Details

<b>HP 9500 48-port 1000BASE-X SFP Advanced Module (JC471A)</b>	<b>Ports</b>	48 SFP 100/1000 Mbps ports
	<b>Physical characteristics</b>	Dimensions 14.96(d) x 15.75(w) x 1.57(h) in. (38 x 40 x 4 cm)  Weight 7.67 lb. (3.48 kg)
	<b>Services</b>	Refer to the HP website at <a href="http://www.hp.com/networking/services">www.hp.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

<b>HP 9500 48-port Gig-T Advanced Module (JC115A)</b>	<b>Ports</b>	48 RJ-45 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only
	<b>Physical characteristics</b>	Dimensions 14.96(d) x 15.75(w) x 1.57(h) in. (38 x 40 x 4 cm)  Weight 6.94 lb. (3.15 kg)
	<b>Services</b>	Refer to the HP website at <a href="http://www.hp.com/networking/services">www.hp.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

<b>HP 9500 24-port GbE SFP Advanced Module (JC117A)</b>	<b>Ports</b>	16 SFP 100/1000 Mbps ports 8 dual-personality ports; 1000M Combo ports (SFP or RJ-45)
	<b>Physical characteristics</b>	Dimensions 14.96(d) x 15.75(w) x 1.57(h) in. (38 x 40 x 4 cm)  Weight 6.99 lb. (3.17 kg)
	<b>Services</b>	Refer to the HP website at <a href="http://www.hp.com/networking/services">www.hp.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

<b>HP 9500 24-port Gig-T Advanced Module (JC119A)</b>	<b>Ports</b>	16 RJ-45 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only 8 dual-personality ports; 1000M Combo ports (SFP or RJ-45)
	<b>Physical characteristics</b>	Dimensions 14.96(d) x 15.75(w) x 1.57(h) in. (38 x 40 x 4 cm)  Weight 6.83 lb. (3.10 kg)
	<b>Services</b>	Refer to the HP website at <a href="http://www.hp.com/networking/services">www.hp.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

### Accessory Product Details

<b>HP 9500 4-port 10GbE XFP Advanced Module (JC118A)</b>	<b>Ports</b>	4 XFP 10-GbE ports; Duplex: full only	
	<b>Physical characteristics</b>	<b>Dimensions</b>	14.96(d) x 15.75(w) x 1.57(h) in. (38 x 40 x 4 cm)
		<b>Weight</b>	6.99 lb. (3.17 kg)
<b>Services</b>	Refer to the HP website at <a href="http://www.hp.com/networking/services">www.hp.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.		

<b>HP 9500 2-port 10GBASE-X XFP Advanced Module (JC470A)</b>	<b>Ports</b>	2 XFP 10-GbE ports; Duplex: full only	
	<b>Physical characteristics</b>	<b>Dimensions</b>	14.96(d) x 15.75(w) x 1.57(h) in. (38 x 40 x 4 cm)
		<b>Weight</b>	6.66 lb. (3.02 kg)
<b>Services</b>	Refer to the HP website at <a href="http://www.hp.com/networking/services">www.hp.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.		

<b>HP X125 1G SFP RJ45 T Transceiver (JD089B)</b>  A small form factor pluggable (SFP) Gigabit 1000Base-T transceiver that provides a full duplex Gigabit solution up to 100m on a Cat-5+ cable.	<b>Ports</b>	1 RJ-45 1000BASE-T port (IEEE 802.3ab Type 1000BASE-T)		
	<b>Connectivity</b>	<b>Connector type</b>	RJ-45	
	<b>Physical characteristics</b>	<b>Dimensions</b>	2.71(d) x 0.54(w) x 0.55(h) in. (6.88 x 1.37 x 1.4 cm)	
		<b>Full configuration weight</b>	0.07 lb. (0.03 kg)	
	<b>Electrical characteristics</b>	<b>Power consumption typical</b>	0.8 W	
		<b>Power consumption maximum</b>	1.0 W	
	<b>Cabling</b>	Cable type: 1000BASE-T: Category 5 (5E or better recommended), 100 Ω differential 4-pair unshielded twisted pair (UTP) or shielded twisted pair (STP) balanced, complying with IEEE 802.3ab 1000BASE-T;		
	<b>Services</b>	Maximum distance: • 100m  Refer to the HP website at <a href="http://www.hp.com/networking/services">www.hp.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.		

### Accessory Product Details

<b>HP X120 1G SFP LC SX Transceiver (JD118B)</b>	<b>Ports</b>	1 LC 1000BASE-SX port
	<b>Connectivity</b>	<b>Connector type</b> LC
<p>A small form-factor pluggable (SFP) Gigabit SX transceiver that provides a full-duplex Gigabit solution up to 550m on a Multimode fiber.</p>	<b>Physical characteristics</b>	<b>Wavelength</b> 850 nm
	<b>Electrical characteristics</b>	<b>Dimensions</b> 2.17(d) x 0.6(w) x 0.46(h) in. (5.51 x 1.52 x 1.17 cm)
		<b>Full configuration weight</b> 0.04 lb. (0.02 kg)
		<b>Power consumption typical</b> 0.8 W
<b>Cabling</b>		<b>Power consumption maximum</b> 1.0 W
		Maximum distance: <ul style="list-style-type: none"> <li>• FDDI Grade distance = 220m</li> <li>• OM1 = 275m</li> <li>• OM2 = 500m</li> <li>• OM3 = Not Specified by standard</li> </ul>
<b>Services</b>		Cable length up to 550m
		Fiber type Multi Mode
		Refer to the HP website at <a href="http://www.hp.com/networking/services">www.hp.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

<b>HP X120 1G SFP LC LX Transceiver (JD119B)</b>	<b>Ports</b>	1 SFP 1000BASE-LX port (IEEE 802.3z Type 1000BASE-LX)
	<b>Connectivity</b>	<b>Connector type</b> LC
<p>A small form-factor pluggable (SFP) Gigabit LX transceiver that provides a full duplex Gigabit solution up to 550m on MMF or 10Km on SMF</p>	<b>Physical characteristics</b>	<b>Wavelength</b> 1300 nm
	<b>Electrical characteristics</b>	<b>Dimensions</b> 2.17(d) x 0.6(w) x 0.46(h) in. (5.51 x 1.52 x 1.17 cm)
		<b>Full configuration weight</b> 0.04 lb. (0.02 kg)
		<b>Power consumption typical</b> 0.8 W
<b>Cabling</b>		<b>Power consumption maximum</b> 1.0 W
		Cable type: Either single mode or multimode;
<b>Services</b>		Maximum distance: <ul style="list-style-type: none"> <li>• 550m for Multimode</li> <li>• 10km for Singlemode</li> </ul>
		Fiber type Both
		Refer to the HP website at <a href="http://www.hp.com/networking/services">www.hp.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

### Accessory Product Details

<b>HP X124 1G SFP LC LH40 1310nm Transceiver</b> (JD061A)	<b>Ports</b>	1 LC 1000Base-LH port (no IEEE standard exists for 1550 nm optics)	
	<b>Connectivity</b>	Connector type	LC
A small form-factor pluggable SFP Gigabit LH40 transceiver that provides a full duplex Gigabit solution up to 40km on a single-mode fiber.	<b>Physical characteristics</b>	Wavelength	1310 nm
		Dimensions	2.17(d) x 0.6(w) x 0.46(h) in. (5.51 x 1.52 x 1.17 cm)
	<b>Electrical characteristics</b>	Full configuration weight	0.04 lb. (0.02 kg)
		Power consumption typical	0.8 W
	<b>Cabling</b>	Power consumption maximum	1.0 W
		Cable type:	Single-mode fiber optic, complying with ITU-T G.652;
	<b>Services</b>	Maximum distance:	
			<ul style="list-style-type: none"> <li>● 40km distance</li> </ul>
		Fiber type	Single Mode
		Refer to the HP website at <a href="http://www.hp.com/networking/services">www.hp.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.	

<b>HP X120 1G SFP LC LH40 1550nm Transceiver</b> (JD062A)	<b>Ports</b>	1 LC 1000BASE-LH port (no IEEE standard exists for 1550 nm optics)	
	<b>Connectivity</b>	Connector type	LC
A small form-factor pluggable (SFP) Gigabit LH40 transceiver that provides a full-duplex Gigabit solution up to 40 km on a single mode fiber.	<b>Physical characteristics</b>	Wavelength	1550 nm
		Dimensions	2.17(d) x 0.6(w) x 0.46(h) in. (5.51 x 1.52 x 1.17 cm)
	<b>Electrical characteristics</b>	Full configuration weight	0.04 lb. (0.02 kg)
		Power consumption typical	0.8 W
	<b>Cabling</b>	Power consumption maximum	1.0 W
		Cable type:	Single-mode fiber optic, complying with ITU-T G.652;
	<b>Services</b>	Maximum distance:	
			<ul style="list-style-type: none"> <li>● 40km distance</li> </ul>
		Fiber type	Single Mode
		Refer to the HP website at <a href="http://www.hp.com/networking/services">www.hp.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.	

### Accessory Product Details

#### HP X125 1G SFP LC LH70 Transceiver (JD063B)

A small form-factor pluggable (SFP) Gigabit LH70 transceiver that provides a full-duplex Gigabit solution up to 70km on a single-mode fiber.

<b>Ports</b>	1 LC 1000BASE-LH port (no IEEE standard exists for 1550 nm optics)
<b>Connectivity</b>	<b>Connector type</b> LC
	<b>Wavelength</b> 1550 nm
<b>Physical characteristics</b>	<b>Dimensions</b> 2.17(d) x 0.6(w) x 0.46(h) in. (5.51 x 1.52 x 1.17 cm)
	<b>Full configuration weight</b> 0.04 lb. (0.02 kg)
<b>Electrical characteristics</b>	<b>Power consumption typical</b> 0.8 W
	<b>Power consumption maximum</b> 1.0 W
<b>Cabling</b>	Cable type: Single-mode fiber optic, complying with ITU-T G.652;
	Maximum distance: • 70km
	Fiber type Single Mode
<b>Services</b>	Refer to the HP website at <a href="http://www.hp.com/networking/services">www.hp.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

#### HP X120 1G SFP LC LH100 Transceiver (JD103A)

A small form factor pluggable (SFP) Gigabit LH100 transceiver that provides a full-duplex Gigabit solution up to 100km on a single mode fiber.

<b>Ports</b>	1 LC 1000BASE-LH port (no IEEE standard exists for 1550 nm optics)
<b>Connectivity</b>	<b>Connector type</b> LC
	<b>Wavelength</b> 1550 nm
<b>Electrical characteristics</b>	<b>Power consumption typical</b> 0.8 W
	<b>Power consumption maximum</b> 1.0 W
<b>Cabling</b>	Cable type: Single-mode fiber optic, complying with ITU-T G.652;
	Maximum distance: • Up to 100km
	Fiber type Single Mode
<b>Services</b>	Refer to the HP website at <a href="http://www.hp.com/networking/services">www.hp.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

### Accessory Product Details

<p><b>HP X120 1G SFP LC BX 10-U Transceiver (JD098B)</b></p> <p>A small form-factor pluggable (SFP) Gigabit LX-BX10-U transceiver that provides a full duplex Gigabit solution up to 10km on a single mode cable.</p>	<p><b>Ports</b></p> <p>1 LC 1000BASE-BX10 port (IEEE 802.3ah Type 1000BASE-BX10-U); Duplex: full only</p> <p><b>Connectivity</b></p> <p><b>Connector type</b> LC</p> <p><b>Physical characteristics</b></p> <p><b>Dimensions</b> 2.17(d) x 0.6(w) x 0.46(h) in. (5.51 x 1.52 x 1.17 cm)</p> <p><b>Full configuration weight</b> 0.04 lb. (0.02 kg)</p> <p><b>Electrical characteristics</b></p> <p><b>Power consumption typical</b> 0.8 W</p> <p><b>Power consumption maximum</b> 1.0 W</p> <p><b>Cabling</b></p> <p>Maximum distance:</p> <ul style="list-style-type: none"> <li>• 10km</li> </ul> <p>Fiber type Single Mode</p> <p><b>Notes</b></p> <p>TX 1310nm RX 1490nm</p> <p><b>Services</b></p> <p>Refer to the HP website at: <a href="http://www.hp.com/networking/services">www.hp.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.</p>
---	---

<p><b>HP X120 1G SFP LC BX 10-D Transceiver (JD099B)</b></p> <p>A small form-factor pluggable (SFP) Gigabit LX-BX10-D transceiver that provides a full duplex Gigabit solution up to 10km on a single mode cable.</p>	<p><b>Ports</b></p> <p>1 LC 1000BASE-BX10 port (IEEE 802.3ah Type 1000BASE-BX10-D); Duplex: full only</p> <p><b>Connectivity</b></p> <p><b>Connector type</b> LC</p> <p><b>Physical characteristics</b></p> <p><b>Dimensions</b> 2.17(d) x 0.6(w) x 0.46(h) in. (5.51 x 1.52 x 1.17 cm)</p> <p><b>Full configuration weight</b> 0.04 lb. (0.02 kg)</p> <p><b>Electrical characteristics</b></p> <p><b>Power consumption typical</b> 0.8 W</p> <p><b>Power consumption maximum</b> 1.0 W</p> <p><b>Cabling</b></p> <p>Maximum distance:</p> <ul style="list-style-type: none"> <li>• Up to 10km</li> </ul> <p>Fiber type Single Mode</p> <p><b>Notes</b></p> <p>TX 1490nm RX 1310nm</p> <p><b>Services</b></p> <p>Refer to the HP website at: <a href="http://www.hp.com/networking/services">www.hp.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.</p>
---	---

### Accessory Product Details

**HP 50 m Multimode OM3 Cabling**  
**LC/LC Optical Cable**  
(AJ839A)

**Cable type:**

50/125  $\mu\text{m}$  (core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m;

**Maximum distance:**

10Gbps Transfer Rate (Ethernet): 300m

**Notes**

Cable Specs: Tight buffered duplex fiber optic multimode OM3 50/125  $\mu\text{m}$  fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.

- Dimensions: Core diameter:  $50 \pm 3.0\mu\text{m}$  Cladding diameter:  $125 \pm 2.0\mu\text{m}$  Coating diameter:  $245 \pm 10\mu\text{m}$
- Optical Glass Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
- Optical Glass: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: Shall achieve 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.
- CABLE: The cable is duplex zipcord graded index 50/125 $\mu\text{m}$  multimode optical fiber. The cable is designed to work in both the 850 and 1300 nm wavelength windows.
- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

**Services**

Refer to the HP website at [www.hp.com/networking/services](http://www.hp.com/networking/services) for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

### Accessory Product Details

**HP 30 m Multimode OM3 Cabling**  
**LC/LC Optical Cable**  
(AJ838A)

**Cable type:**

50/125  $\mu\text{m}$  (core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m;

**Maximum distance:**

10Gbps Transfer Rate (Ethernet): 300m

**Notes**

Cable Specs: Tight buffered duplex fiber optic multimode OM3 50/125  $\mu\text{m}$  fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.

- Dimensions: Core diameter:  $50 \pm 3.0\mu\text{m}$  Cladding diameter:  $125 \pm 2.0\mu\text{m}$  Coating diameter:  $245 \pm 10\mu\text{m}$
- Optical Glass Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
- Optical Glass: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: Shall achieve 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.
- CABLE: The cable is duplex zipcord graded index 50/125 $\mu\text{m}$  multimode optical fiber. The cable is designed to work in both the 850 and 1300 nm wavelength windows.
- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

**Services**

Refer to the HP website at [www.hp.com/networking/services](http://www.hp.com/networking/services) for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

### Accessory Product Details

**HP 15 m Multimode OM3 Cabling**  
**LC/LC Optical Cable**  
(AJ837A)

**Cable type:**

50/125  $\mu\text{m}$  (core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m;

**Maximum distance:**

10Gbps Transfer Rate (Ethernet): 300m

**Notes**

Cable Specs: Tight buffered duplex fiber optic multimode OM3 50/125  $\mu\text{m}$  fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.

- Dimensions: Core diameter:  $50 \pm 3.0\mu\text{m}$  Cladding diameter:  $125 \pm 2.0\mu\text{m}$  Coating diameter:  $245 \pm 10\mu\text{m}$
- Optical Glass Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
- Optical Glass: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: Shall achieve 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.
- CABLE: The cable is duplex zipcord graded index 50/125 $\mu\text{m}$  multimode optical fiber. The cable is designed to work in both the 850 and 1300 nm wavelength windows.
- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

**Services**

Refer to the HP website at [www.hp.com/networking/services](http://www.hp.com/networking/services) for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

### Accessory Product Details

**HP 5 m Multimode OM3 LC/LC Optical Cable**  
(AJ836A)

**Cabling**

**Cable type:**

50/125 µm core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m;

**Maximum distance:**

10Gbps Transfer Rate (Ethernet): 300m

**Notes**

Cable Specs: This specification defines the detail requirements for a tight buffered duplex fiber optic multimode OM3 50/125 um fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.

- Dimensions: Core diameter: 50 ± 3.0um Cladding diameter: 125 ± 2.0um Coating diameter: 245 ± 10um
- Optical Glass Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
- Optical Glass: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: Shall achieve 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.
- CABLE: The cable is duplex zipcord graded index 50/125um multimode optical fiber. The cable is designed to work in both the 850 and 1300 nm wavelength windows.
- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

**Services**

Refer to the HP website at [www.hp.com/networking/services](http://www.hp.com/networking/services) for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

### Accessory Product Details

**HP 2 m Multimode OM3 LC/LC Optical Cable**  
(AJ835A)

**Cabling**

**Cable type:**

50/125  $\mu\text{m}$  (core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m;

**Maximum distance:**

10Gbps Transfer Rate (Ethernet): 300m

**Notes**

Cable Specs: Tight buffered duplex fiber optic multimode OM3 50/125  $\mu\text{m}$  fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.

- Dimensions: Core diameter:  $50 \pm 3.0\mu\text{m}$  Cladding diameter:  $125 \pm 2.0\mu\text{m}$  Coating diameter:  $245 \pm 10\mu\text{m}$
- Optical Glass Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
- Optical Glass: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: Shall achieve 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.
- CABLE: The cable is duplex zipcord graded index 50/125 $\mu\text{m}$  multimode optical fiber. The cable is designed to work in both the 850 and 1300 nm wavelength windows.
- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

**Services**

Refer to the HP website at [www.hp.com/networking/services](http://www.hp.com/networking/services) for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

### Accessory Product Details

**HP 1 m Multimode OM3 LC/LC Optical Cable**  
(AJ834A)

**Cabling**

**Cable type:**

50/125  $\mu\text{m}$  (core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m

**Maximum distance:**

10Gbps Transfer Rate (Ethernet): 300m

**Notes**

Cable Specs: Tight buffered duplex fiber optic multimode OM3 50/125  $\mu\text{m}$  fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.

- Dimensions: Core diameter:  $50 \pm 3.0\mu\text{m}$  Cladding diameter:  $125 \pm 2.0\mu\text{m}$  Coating diameter:  $245 \pm 10\mu\text{m}$
- Optical Glass Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
- Optical Glass: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: Shall achieve 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.
- CABLE: The cable is duplex zipcord graded index 50/125 $\mu\text{m}$  multimode optical fiber. The cable is designed to work in both the 850 and 1300 nm wavelength windows.
- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

**Services**

Refer to the HP website at [www.hp.com/networking/services](http://www.hp.com/networking/services) for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

### Accessory Product Details

**HP 0.5 m Multimode OM3 Cabling  
LC/LC Optical Cable  
(AJ833A)**

**Cable type:**

50/125 µm (core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m

**Maximum distance:**

10Gbps Transfer Rate (Ethernet): 300m

**Notes**

Cable Specs: Tight buffered duplex fiber optic multimode OM3 50/125 µm fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.

- Dimensions: Core diameter: 50 ± 3.0µm Cladding diameter: 125 ± 2.0µm Coating diameter: 245 ± 10µm
- Optical glass: Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
- Optical glass: Bandwidth: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.
- CABLE: The cable is duplex zipcord graded index 50/125µm multimode optical fiber and designed to work in both the 850 and 1300 nm wavelength windows.
- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

**Services**

Refer to the HP website at [www.hp.com/networking/services](http://www.hp.com/networking/services) for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

### Accessory Product Details

**HP Premier Flex LC/LC  
Multi-mode OM4 2 fiber  
1m Cable (QK732A)**

**Notes**

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core Diameter: 50um ±3um, Cladding diameter: 125um ±2um; Coating diameter: 245 ± 10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HP PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m addec for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

**Services**

Refer to the HP website at [www.hp.com/networking/services](http://www.hp.com/networking/services) for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

**HP Premier Flex LC/LC  
Multi-mode OM4 2 fiber  
2m Cable (QK733A)**

**Notes**

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core diameter: 50um ±3um, Cladding diameter: 125um ±2um; Coating diameter: 245 ± 10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HP PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m addec for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

**Services**

Refer to the HP website at [www.hp.com/networking/services](http://www.hp.com/networking/services) for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

### Accessory Product Details

**HP Premier Flex LC/LC  
Multi-mode OM4 2 fiber  
5m Cable (QK734A)**

**Notes**

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core diameter: 50um ±3um, Cladding diameter: 125um ±2um; Coating diameter: 245 ± 10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HP PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m addec for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

**Services**

Refer to the HP website at [www.hp.com/networking/services](http://www.hp.com/networking/services) for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

**HP Premier Flex LC/LC  
Multi-mode OM4 2 fiber  
15m Cable (QK735A)**

**Notes**

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core diameter: 50um ±3um, Cladding diameter: 125um ±2um; Coating diameter: 245 ± 10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HP PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m addec for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

**Services**

Refer to the HP website at [www.hp.com/networking/services](http://www.hp.com/networking/services) for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

### Accessory Product Details

**HP Premier Flex LC/LC  
Multi-mode OM4 2 fiber  
30m Cable (QK736A)**

**Notes**

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core diameter: 50um ±3um, Cladding diameter: 125um ±2um; Coating diameter: 245 ± 10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HP PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m addec for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

**Services**

Refer to the HP website at [www.hp.com/networking/services](http://www.hp.com/networking/services) for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

**HP Premier Flex LC/LC  
Multi-mode OM4 2 fiber  
50m Cable (QK737A)**

**Notes**

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core diameter: 50um ±3um, Cladding diameter: 125um ±2um; Coating diameter: 245 ± 10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HP PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m addec for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

**Services**

Refer to the HP website at [www.hp.com/networking/services](http://www.hp.com/networking/services) for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

**HP 9500 Access Controller Ports  
Module for 128-640  
Access Points (JD442A)**

- 1 RJ-45 serial console port
- 1 RJ-45 out-of-band management port
- 2 USB 1.0 12 Mbps ports

**Physical characteristics**

- Dimensions** 14.45(d) x 13.39(w) x 1.6(h) in. (36.7 x 34 x 4.06 cm) (1U height)
- Weight** 7.89 lb. (3.58 kg)

### Accessory Product Details

<b>Memory and processor</b>	<b>Processor</b>	Eight core @ 950 MHz, 256 MB compact flash, 1 GB DDR2 DIMM
<b>Performance</b>	<b>Switch fabric speed</b>	20 Gbps
	<b>MAC address table size</b>	24,000 entries
<b>Environment</b>	<b>Operating temperature</b>	32°F to 113°F (0°C to 45°C)
	<b>Operating relative humidity</b>	5% to 95%, non-condensing
	<b>Non-operating/Storage temperature</b>	-40°F to 158°F (-40°C to 70°C)
	<b>Non-operating/Storage relative humidity</b>	5% to 95%, non-condensing
<b>Electrical characteristics</b>	<b>Maximum heat dissipation</b>	358 BTU/hr (377.69 kJ/hr)
	<b>Maximum power rating</b>	105 W
<b>Safety</b>	UL 60950-1; EN 60950-1; CAN/CSA-C22.2 No. 60950-1; Anatel; GOST; C-Tick; NOM; IEC 60950-1 (with CB report)	
<b>Emissions</b>	EN 55022; VCCI; ICES-003; AS/NZS CISPR 22; EN 300 386; FCC Part 15; EN 61000-3-2:2006; EN 61000-3-3:1995 +A1:2001+A2:2005; EMC Directive 2004/108/EC	
<b>Immunity</b>	<b>EN</b>	EN 61000-4-2:1995+A1:1998+A2:2001; EN 61000-4-3:2006; EN 61000-4-4:2004; EN 61000-4-5:2006; EN 61000-4-6: 1996 +A1:2001:A2:2007; EN 61000-4-8:2001; EN 61000-4-11:2004; EN 55024:1998+ A1:2001 + A2:2003
<b>Management</b>	IMC - Intelligent Management Center; command-line interface; Web browser; configuration menu; SNMP Manager; Telnet; HTTPS; RMON1; FTP; in-line and out-of-band; IEEE 802.3 Ethernet MIB; Ethernet Interface MIB	
<b>Features</b>	A9500 ACM License system	
	<ul style="list-style-type: none"> <li>The A9500 ACM is an access controller module for the HP A9500 series Ethernet switches. It supports 128 APs by default. After license upgrade, the access controller module can support up to 640 APs.</li> </ul>	
<b>Notes</b>	Max. number of users: 20K. Max. number of users that are supported by local authentication: 1K. Max. number of SSIDs that can be configured: 512. Max. number of users that are supported by local portal authentication: 4K. Number of ACLs: 32K.	
<b>Services</b>	Refer to the HP website at: <a href="http://www.hp.com/networking/services">www.hp.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.	
<b>Standards and protocols</b>	<b>General protocols</b>	<b>MIBs</b>
	RFC 768 UDP	RFC 1229 Interface MIB Extensions
	RFC 791 IP	RFC 1643 Ethernet MIB
	RFC 792 ICMP	RFC 1757 Remote Network Monitoring MIB
	RFC 793 TCP	

### Accessory Product Details

RFC 826 ARP	RFC 2011 SNMPv2 MIB for IP
RFC 854 TELNET	RFC 2012 SNMPv2 MIB for TCP
RFC 855 Telnet Option Specification	RFC 2013 SNMPv2 MIB for UDP
RFC 858 Telnet Suppress Go Ahead Option	RFC 2571 SNMP Framework MIB
RFC 894 IP over Ethernet	RFC 2572 SNMP-MPD MIB
RFC 950 Internet Standard Subnetting Procedure	RFC 2613 SMON MIB
RFC 959 File Transfer Protocol (FTP)	RFC 2863 The Interfaces Group MIB
RFC 1122 Host Requirements	RFC 2932IP (Multicast Routing MIB)
RFC 1141 Incremental updating of the Internet checksum	RFC 2933 IGMP MIB
RFC 1144 Compressing TCP/IP headers for low-speed serial links	<b>Mobility</b>
RFC 1256 ICMP Router Discovery Protocol (IRDP)	IEEE 802.11a High Speed Physical Layer in the 5 GHz Band
RFC 1321 The MD5 Message-Digest Algorithm	IEEE 802.11b Higher-Speed Physical Layer Extension in the 2.4 GHz Band
RFC 1334 PPP Authentication Protocols (PAP)	IEEE 802.11d Global Harmonization
RFC 1350 TFTP Protocol (revision 2)	IEEE 802.11g Further Higher Data Rate Extension in the 2.4 GHz Band
RFC 1812 IPv4 Routing	IEEE 802.11i Medium Access Control (MAC) Security Enhancements
RFC 1944 Benchmarking Methodology for Network Interconnect Devices	IEEE 802.11n WLAN Enhancements for Higher Throughput
RFC 1994 PPP Challenge Handshake Authentication Protocol (CHAP)	<b>Network management</b>
RFC 2104 HMAC: Keyed-Hashing for Message Authentication	RFC 1155 Structure of Management Information
RFC 2246 The TLS Protocol Version 1.0	RFC 1905 SNMPv2 Protocol Operations
RFC 2284 EAP over LAN	RFC 2573 SNMPv3 Applications
RFC 2644 Directed Broadcast Control	RFC 2574 SNMPv3 User-based Security Model (USM)
RFC 2864 The Inverted Stack Table Extension to the Interfaces Group MIB	RFC 2575 VACM for SNMP SNMPv1/v2c
RFC 2866 RADIUS Accounting	<b>QoS/CoS</b>
RFC 2869 RADIUS Extensions	RFC 2474 DS Field in the IPv4 and IPv6 Headers
RFC 3268 Advanced Encryption Standard (AES) Ciphersuites for Transport Layer Security (TLS)	RFC 2475 DiffServ Architecture
RFC 3619 Ethernet Automatic Protection Switching (EAPS)	RFC 3168 The Addition of Explicit Congestion Notification (ECN) to IP
draft-ietf-capwap-protocol-specification-00.txt:CAPW	<b>Security</b>
	IEEE 802.1X Port Based Network Access Control

### Accessory Product Details

AP Protocol Specification  
draft-ohara-capwap-lwapp-  
03.txt:Light Weight  
Access Point Protocol

#### **IP multicast**

RFC 1112 IGMP  
RFC 2236 IGMPv2  
RFC 2934 Protocol Independent  
Multicast MIB for  
IPv4

#### **IPv6**

RFC 1350 TFTP  
RFC 1881 IPv6 Address Allocation  
Management  
RFC 1887 IPv6 Unicast Address  
Allocation  
Architecture  
RFC 1981 IPv6 Path MTU Discovery  
RFC 2292 Advanced Sockets API for  
IPv6  
RFC 2373 IPv6 Addressing Architecture  
RFC 2375 IPv6 Multicast Address  
Assignments  
RFC 2460 IPv6 Specification  
RFC 2461 IPv6 Neighbor Discovery  
RFC 2462 IPv6 Stateless Address  
Auto-configuration  
RFC 2463 ICMPv6  
RFC 2464 Transmission of IPv6 over  
Ethernet  
Networks  
RFC 2526 Reserved IPv6 Subnet  
Anycast Addresses  
RFC 2563 ICMPv6  
RFC 2925 Definitions of Managed  
Objects for  
Remote Ping, Traceroute, and Lookup  
Operations  
(Ping only)  
RFC 3484 Default Address Selection  
for IPv6  
RFC 3587 IPv6 Global Unicast Address  
Format  
RFC 4443 ICMPv6  
RFC 4541 IGMP & MLD Snooping  
Switch  
RFC 4861 IPv6 Neighbor Discovery  
RFC 4862 IPv6 Stateless Address

Standard (AES)  
Key Wrap Algorithm  
RFC 3579 RADIUS Support For  
Extensible  
Authentication Protocol (EAP)  
Access Control Lists (ACLs)  
Guest VLAN for 802.1x  
MAC Authentication  
Secure Sockets Layer (SSL)  
SSHv1.5 Secure Shell  
SSHv2 Secure Shell  
Web Authentication  
WPA (Wi-Fi Protected Access)/WPA2

#### **IKEv1**

RFC 3748 - Extensible Authentication  
Protocol (EAP)

### Accessory Product Details

Auto-configuration  
RFC 5095 Deprecation of Type 0  
Routing Headers  
in IPv6

<b>HP 9500 VPN Firewall Module (JD245A)</b>	<b>Ports</b>	2 RJ-45 auto-negotiating 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T) 2 dual-personality ports; auto-sensing 10/100/1000Base-T or SFP 1 RJ-45 serial console port 1 Compact Flash port				
	<b>Physical characteristics</b>	<table border="0"> <tr> <td style="vertical-align: top;">Dimensions</td> <td>15.71(w) x 14.92(d) x 1.58(h) in (39.9 x 37.9 x 4.01 cm)</td> </tr> <tr> <td style="vertical-align: top;">Weight</td> <td>7.72 lb (3.5 kg)</td> </tr> </table>	Dimensions	15.71(w) x 14.92(d) x 1.58(h) in (39.9 x 37.9 x 4.01 cm)	Weight	7.72 lb (3.5 kg)
Dimensions	15.71(w) x 14.92(d) x 1.58(h) in (39.9 x 37.9 x 4.01 cm)					
Weight	7.72 lb (3.5 kg)					
	<b>Environment</b>	<table border="0"> <tr> <td style="vertical-align: top;">Operating temperature</td> <td>32°F to 113°F (0°C to 45°C)</td> </tr> <tr> <td style="vertical-align: top;">Operating relative humidity</td> <td>10% to 95%, noncondensing</td> </tr> </table>	Operating temperature	32°F to 113°F (0°C to 45°C)	Operating relative humidity	10% to 95%, noncondensing
Operating temperature	32°F to 113°F (0°C to 45°C)					
Operating relative humidity	10% to 95%, noncondensing					
	<b>Management</b>	IMC - Intelligent Management Center; command-line interface; Web browser; SNMP Manager; Telnet; HTTPS; RMON1; FTP				
	<b>Features</b>	<p>PerfoPerformance</p> <ul style="list-style-type: none"> <li>- 8Gbps Firewall Throughput</li> <li>- 2M Concurrent connection</li> <li>- 60K New connection per second</li> <li>- Max 20480 security policies</li> <li>- 2Gbps 3DES/AES VPN Throughput</li> <li>- 5000 IPsec tunnel</li> <li>- 4K VLAN</li> </ul> <p>Firewall operation mode</p> <ul style="list-style-type: none"> <li>- Routing mode</li> <li>- Transparent mode</li> <li>- Hybrid mode</li> </ul> <p>AAA service</p> <ul style="list-style-type: none"> <li>- Local Authentication</li> <li>- Standard Radius</li> <li>- HWTACACS+</li> <li>- RADIUS domain Authentication</li> </ul> <p>ASPF</p> <ul style="list-style-type: none"> <li>- General TCP / UDP application</li> <li>- FTP/SMTP/HTTP/RTSP/H323 Protocol State Detection</li> <li>- SIP/MGCP/QQ/MSN Protocol State Detection</li> <li>- Java/ActiveX Blocking and Detection</li> <li>- Port mapping</li> <li>- Support for the fragmented packets</li> </ul> <p>Virtualization</p> <ul style="list-style-type: none"> <li>- 256 Virtual Firewall</li> <li>- 4 default Security Zone</li> <li>- Max 256 Security Zone</li> </ul> <p>NAT</p> <ul style="list-style-type: none"> <li>- NAT</li> </ul>				

### Accessory Product Details

- PAT
- NAT Server
- Port mapping
- Bidirectional NAT
- Static NAT
- Network Security
- Add blacklist by hand or automatically
- IP+MAC Binding
- ARP Reverse Query
- ARP Cheat Check
- Management ports closed by default
- DDOS
- DNS Query Flood
- SYN Flood
- Auto start TCP Proxy when Detect SYN Flood
- ICMP Flood
- UDP Flood
- IP Spoofing
- SQL injection filter
- L2TP VPN
- LNS,LAC
- L2TP Multi-instance
- GRE
- GRE tunneling protocol
- IPSec
- AH/ESP
- ESP
- Transport/tunnel
- NAT traversal
- Strategy template
- IKE
- DH
- Pre-share Key authentication-method
- Support aggressive mode and main exchange mode
- IKE DPD, PKI / CA
- Network Feature
- 802.1q VLAN
- 4K sub-interface
- Static and dynamic ARP
- Multicast, PIM
- IGMP v1/v2/v3
- Routing
- RIP
- OSPF
- BGP
- Static Route
- policy Route
- High Availability
- Active/Active mode
- Active/Passive mode

### Accessory Product Details

- Session Synchronization for Firewall System management
- Web Management support IE/Firefox
- Command line interface (Console/Telnet/SSH)
- Classification Manager
- Unified management through iMC
- SNMP v2c/v3
- Administration
  - Software Upgrades
  - Configuration Backup and Restore
- Logging/Monitoring
  - Syslog
  - Mini RMON
  - NTP
  - NAT/ASPF/firewall log stream(Binary log)
- IPv6 Routing & Multicast
  - RIPng
  - OSPFv3
  - BGP4+
  - Static Route
  - Policy Route
  - PIM-SM/DM
- IPv6 Security
  - NAT-PT
  - Manual tunnel
  - IPV6 OVER ipv4 GRE tunnel
  - 6to4 tunnel (RFC3056)
  - ISATAP Tunnel
  - IPv6 Packet Filter
  - Radius
  - NAT64

### Services

- 3-year, parts only, global next-day advance exchange (UZ896E)
- 3-year, 4-hour onsite, 13x5 coverage for hardware (UZ897E)
- 3-year, 4-hour onsite, 24x7 coverage for hardware (UZ900E)
- 3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 SW phone support and SW updates (UZ904E)
- 3-year, 24x7 SW phone support, software updates (UZ907E)
- 1-year, post-warranty, 4-hour onsite, 13x5 coverage for hardware (HR735E)
- 1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware (HR736E)
- 1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (HR737E)
- 4-year, 4-hour onsite, 13x5 coverage for hardware (UZ898E)
- 4-year, 4-hour onsite, 24x7 coverage for hardware (UZ901E)
- 4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UZ941E)
- 4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UZ905E)
- 4-year, 24x7 SW phone support, software updates (UZ908E)
- 5-year, 4-hour onsite, 13x5 coverage for hardware (UZ899E)
- 5-year, 4-hour onsite, 24x7 coverage for hardware (UZ902E)

### Accessory Product Details

5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UZ906E)

5-year, 24x7 SW phone support, software updates (UZ909E)

3 Yr 6 hr Call-to-Repair Onsite (UZ910E)

4 Yr 6 hr Call-to-Repair Onsite (UZ911E)

5 Yr 6 hr Call-to-Repair Onsite (UZ912E)

1-year, 6 hour Call-To-Repair Onsite for hardware (HR739E)

1-year, 24x7 software phone support, software updates (HR738E)

Refer to the HP website at [www.hp.com/networking/services](http://www.hp.com/networking/services) for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

#### **Standards and protocols IPv6**

RFC 1981 IPv6 Path MTU Discovery

RFC 2460 IPv6 Specification

RFC 2465 Management Information Base for IP

Version 6: Textual Conventions and General Group (partially support, only "IPv6 Interface Statistics table")

RFC 3484 Default Address Selection for IPv6

RFC 3513 IPv6 Addressing Architecture

RFC 3587 IPv6 Global Unicast Address Format

RFC 4007 IPv6 Scoped Address Architecture

RFC 4862 IPv6 Stateless Address Auto-configuration

#### **Security**

RFC 1321 The MD5 Message-Digest Algorithm

RFC 1334 PPP Authentication Protocols (PAP)

RFC 1994 PPP Challenge Handshake Authentication Protocol (CHAP)

RFC 2104 Keyed-Hashing for Message Authentication

RFC 2138 RADIUS Authentication

RFC 2618 RADIUS Authentication Client MIB

RFC 2620 RADIUS Accounting Client MIB

RFC 2716 PPP EAP TLS Authentication Protocol

RFC 2865 RADIUS (client only)

RFC 2865 RADIUS Authentication

RFC 2867 RADIUS Accounting Modifications for Tunnel Protocol Support

RFC 2868 RADIUS Attributes for Tunnel Protocol Support

RFC 2869 RADIUS Extensions draft-grant-tacacs-02 (TACACS)

#### **VPN**

RFC 1701 Generic Routing Encapsulation (GRE)

RFC 1702 Generic Routing Encapsulation over IPv4 networks.

RFC 1828 IP Authentication using Keyed MD5

RFC 1829 The ESP DES-CBC Transform

RFC 1853 IP in IP Tunneling

RFC 2085 HMAC-MD5 IP Authentication with Replay Prevention

RFC 2401 Security Architecture for the Internet Protocol

RFC 2402 IP Authentication Header

RFC 2403 - HMAC-MD5-96

RFC 2403 The Use of HMAC-MD5-96 within ESP and AH

### Accessory Product Details

RFC 2404 The Use of HMAC-SHA-1-96 within ESP and AH  
RFC 2405 The ESP DES-CBC Cipher Algorithm With Explicit IV  
RFC 2406 IP Encapsulating Security Payload (ESP)  
RFC 2410 The NULL Encryption Algorithm and Its Use With IPsec  
RFC 2411 IP Security Document Roadmap  
RFC 2451 The ESP CBC-Mode Cipher Algorithms  
RFC 2473 Generic Packet Tunneling in IPv6 Specification  
RFC 2529 Transmission of IPv6 over IPv4 Domains without Explicit Tunnels  
RFC 2661 Layer Two Tunneling Protocol "L2TP"  
RFC 2784 Generic Routing Encapsulation (GRE)  
RFC 2868 RADIUS Attributes for Tunnel Protocol Support  
RFC 2893 Transition Mechanisms for IPv6 Hosts and Routers  
RFC 3602 The AES-CBC Cipher Algorithm and Its Use with IPsec  
RFC 4214 Intra-Site Automatic Tunnel Addressing Protocol (ISATAP)

#### IKEv1

RFC 2407 The Internet IP Security Domain of Interpretation for ISAKMP  
RFC 2408 Internet Security Association and Key Management Protocol (ISAKMP).  
RFC 2409 The Internet Key Exchange (IKE)  
RFC 2412 The OAKLEY Key Determination Protocol  
RFC 3526 More Modular Exponential (MODP)  
Diffie-Hellman groups for Internet Key Exchange (IKE)  
RFC 3706 A Traffic-Based Method of Detecting Dead Internet Key Exchange (IKE) Peers

#### PKI

RFC 2511 Internet X.509 Certificate Request Message Format  
RFC 3279 Algorithms and Identifiers for the Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile  
RFC 3280 Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile  
draft-nourse-scep-06:  
PKCS#1  
PKCS#10  
PKCS#12  
PKCS#7

---

#### HP 9500 Load Balancing Module (JD247A) Ports

2 RJ-45 auto-negotiating 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T)  
2 dual-personality ports; auto-sensing 10/100/1000Base-T or SFP  
1 RJ-45 serial console port  
1 Compact Flash port

#### Physical characteristics

Dimensions 14.92(d) x 15.71(w) x 1.57(h) in. (37.9 x 39.9 x 4 cm)

### Accessory Product Details

	Weight	7.94 lb. (3.6 kg)
<b>Memory and processor</b>	2 GB DDR2 SDRAM Mb, 4 MB flash	
<b>Environment</b>	Operating temperature	32°F to 113°F (0°C to 45°C)
	Operating relative humidity	10% to 90%, noncondensing
<b>Features</b>	Performance	
	<ul style="list-style-type: none"><li>- 2Gbps throughput</li><li>- Concurrent connections: 2M</li><li>- L4 Connection Per Second: 50K</li><li>- L7 Connection Per Second: 30K</li><li>- Max number of virtual servers: 1K</li><li>- Max number of real server groups: 1K</li><li>- Max number of real servers: 16K</li><li>- Max number of real servers in one real server group: 1K</li></ul>	
	Load balancing scheduling algorithm	
	<ul style="list-style-type: none"><li>- Round robin</li><li>- Weighted round robin</li><li>- Least connections</li><li>- Weighted least connections</li><li>- Random</li><li>- Weighted random</li><li>- Source IP address hashing</li><li>- Destination IP address hashing</li><li>- Source IP-port hashing</li><li>- UDP Packet Load Hash</li><li>- Best-case Response Time</li><li>- L7 Content</li></ul>	
	Health Monitor Algorithm	
	<ul style="list-style-type: none"><li>- ICMP</li><li>- TCP</li><li>- FTP</li><li>- HTTP</li><li>- SSL</li><li>- DNS</li><li>- Radius</li><li>- SMTP</li><li>- POP3</li><li>- RTSP</li><li>- IMAP4</li><li>- SNMP</li><li>- SIP</li></ul>	
	User Session Persistence for L4 Load Balance	
	<ul style="list-style-type: none"><li>- Source IP based</li><li>- Cookie based</li><li>- HTTP Header based</li><li>- Source/Destination IP/ Port/ Port+IP based</li></ul>	
	User session persistence for L7 Load Balance	
	<ul style="list-style-type: none"><li>- HTTP Header based</li><li>- HTTP Cookie</li></ul>	

### Accessory Product Details

- SIP based
- Radius attributes based
- DHCP based
- Real Service Group Method for L7 Load Balance
  - HTTP Request URL-File
  - HTTP Request URL-Function
  - HTTP Host
  - HTTP User-Agent
  - HTTP Accept-Language
  - HTTP Accept-Encoding
  - HTTP Request-Method
  - HTTP header
  - RTSP URL
  - DHCP Relay Agent IP
- IPv6 load balancing algorithm
  - Round Robin
  - Weighted Round Robin
  - Least Connection
  - Weighted Least Connection
  - Random
  - Weighted Random
  - Source IP/IP-Port Hash
  - Destination IP Hash
- IPv6 Health monitoring Algorithm
  - ICMP
  - HTTP
- User-Session Persistence for IPv6
  - Source IP based
- Operation Mode
  - NAT Mode
  - DR Mode
  - Firewall Load Balance
- Security Features
  - ACL
  - NATP
  - PAT
  - NAT Server
  - Port mapping
  - DNS Query Flood
  - SYN Flood
  - ICMP Flood
  - UDP Flood
  - IP Spoofing
  - Hotfix
  - standard Radius
- HA
  - VRRP
  - Dual Hot Standby
  - Configuration Sync
- System Management

### Accessory Product Details

- Web UI
- Command line
- Management at different grades
- SSH1.5
- SSH2.0
- FTP/TFTP/Telnet
- SNMPv1/v2c/v3
- Mini RMON
- NTP
- Log
- Syslog
- NAT/ASPF/Firewall Flow Log

### Services

- 3-year, parts only, global next-day advance exchange (UZ950E)
- 3-year, 4-hour onsite, 13x5 coverage for hardware (UZ951E)
- 3-year, 4-hour onsite, 24x7 coverage for hardware (UZ954E)
- 3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 SW phone support and SW updates (UZ958E)
- 3-year, 24x7 SW phone support, software updates (UZ961E)
- 1-year, post-warranty, 4-hour onsite, 13x5 coverage for hardware (HR750E)
- 1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware (HR751E)
- 1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (HR752E)
- 4-year, 4-hour onsite, 13x5 coverage for hardware (UZ952E)
- 4-year, 4-hour onsite, 24x7 coverage for hardware (UZ955E)
- 4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UZ959E)
- 4-year, 24x7 SW phone support, software updates (UZ962E)
- 5-year, 4-hour onsite, 13x5 coverage for hardware (UZ953E)
- 5-year, 4-hour onsite, 24x7 coverage for hardware (UZ956E)
- 5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UZ960E)
- 5-year, 24x7 SW phone support, software updates (UZ963E)
- 3 Yr 6 hr Call-to-Repair Onsite (UZ964E)
- 4 Yr 6 hr Call-to-Repair Onsite (UZ965E)
- 5 Yr 6 hr Call-to-Repair Onsite (UZ966E)
- 1-year, 6 hour Call-To-Repair Onsite for hardware (HR754E)
- 1-year, 24x7 software phone support, software updates (HR753E)

Refer to the HP website at [www.hp.com/networking/services](http://www.hp.com/networking/services) for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

### HP 9500 NetStream Monitoring Module (JD246A)

### Ports

- 2 RJ-45 auto-negotiating 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T)
- 2 RJ-45 dual-personality ports; auto-sensing 10/100/1000Base-T or SFP
- 1 RJ-45 serial console port
- 1 Compact Flash port

### Accessory Product Details

<b>Physical characteristics</b>	Dimensions	14.92(d) x 15.71(w) x 1.57(h) in. (37.9 x 39.9 x 4 cm)
	Weight	7.28 lb. (3.3 kg)
<b>Memory and processor</b>	2 GB DDR2 SDRAM, 4 MB flash	
<b>Performance</b>	Throughput	4 Gbps
	Concurrent sessions	2.4M
<b>Environment</b>	Operating temperature	32°F to 104°F (0°C to 40°C)
	Operating relative humidity	10% to 90%, noncondensing
<b>Management</b>	IMC - Intelligent Management Center; command-line interface; Web browser; SNMP Manager; Telnet; HTTPS; FTP	
<b>Features</b>	PerConfiguration of NetStream on an interface	
	Setting of the interface sampling mode	
	- Rule-based mode	
	- Random mode	
	Configuration of packet filtering on an interface	
	Configuration of aggregate IP traffic accounting	
	- protocol-port aggregation	
	Setting of buffer size for NetStream data	
	Setting of the output address for NetStream data	
	Setting of the output version	
	Setting of the output rate	
	Setting of the packet refresh rate for templates of NetStream data of version 9	
	Setting of the time refresh rate for templates of NetStream data of version 9	
<b>Services</b>	Aging of NetStream data	
	- Active aging time	
	- Inactive aging time	
	- Forced aging	
	Format of output NetStream data	
	- Version 5	
	- Version 8	
	- Version 9	
	Management mode	
	- CLI (Telnet or SSH)	
	- Support of standard SNMPv3; SNMPv2c and SNMPv1 compatible	
	3-year, parts only, global next-day advance exchange (UZ932E)	
	3-year, 4-hour onsite, 13x5 coverage for hardware (UZ933E)	
3-year, 4-hour onsite, 24x7 coverage for hardware (UZ936E)		
3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 SW phone support and SW updates (UZ940E)		
3-year, 24x7 SW phone support, software updates (UZ943E)		
1-year, post-warranty, 4-hour onsite, 13x5 coverage for hardware (HR745E)		
1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware (HR746E)		
1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (HR747E)		
4-year, 4-hour onsite, 13x5 coverage for hardware (UZ934E)		
4-year, 4-hour onsite, 24x7 coverage for hardware (UZ937E)		

### Accessory Product Details

4-year, 24x7 SW phone support, software updates (UZ944E)  
5-year, 4-hour onsite, 13x5 coverage for hardware (UZ935E)  
5-year, 4-hour onsite, 24x7 coverage for hardware (UZ938E)  
5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UZ942E)  
5-year, 24x7 SW phone support, software updates (UZ945E)  
3 Yr 6 hr Call-to-Repair Onsite (UZ946E)  
4 Yr 6 hr Call-to-Repair Onsite (UZ947E)  
5 Yr 6 hr Call-to-Repair Onsite (UZ948E)  
1-year, 6 hour Call-To-Repair Onsite for hardware (HR749E)  
1-year, 24x7 software phone support, software updates (HR748E)

Refer to the HP website at [www.hp.com/networking/services](http://www.hp.com/networking/services) for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

---

#### HP 9500 720Gbps Fabric Module (JC120A) **Ports**

1 RJ-45 serial console port  
1 RJ-45 out-of-band management port  
1 RJ-45 autosensing 10/100 port (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full  
1 RJ-45 Serial port  
1 Compact Flash port  
1 USB 2.0

**Physical characteristics** Dimensions 15.75(w) x 14.96(d) x 1.57(h) in (40 x 38 x 4 cm)  
Weight 7.83 lb. (3.55 kg)

**Services** Refer to the HP website at [www.hp.com/networking/services](http://www.hp.com/networking/services) for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

---

#### HP 9500 360Gbps Fabric Module (JC121A) **Ports**

1 RJ-45 serial console port  
1 RJ-45 out-of-band management port  
1 RJ-45 autosensing 10/100 port (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full  
1 RJ-45 Serial port  
1 Compact Flash port  
1 USB 2.0

**Physical characteristics** Dimensions 15.75(w) x 14.96(d) x 1.57(h) in (40 x 38 x 4 cm)  
Weight 7.25 lb. (3.29 kg)

**Services** Refer to the HP website at [www.hp.com/networking/services](http://www.hp.com/networking/services) for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

### Accessory Product Details

To learn more, visit: [www.hp.com/networking](http://www.hp.com/networking)

© Copyright 2010-2013 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Windows and Windows Vista are U.S. registered trademarks of Microsoft Corporation.